



## MATERIAL SAFETY DATA SHEET

**Effective Date** July 21, 2008  
**MSDS Number** M119

### Section 1 – Product and Company Information

**Product Name:** Drican® (Indicating Silica gel, Aluminum case)  
**Product Use:** Desiccant, absorbent  
**Grades:** Silica gel, indicating  
**Synonyms:** Amorphous silica gel, SiO<sub>2</sub>, silicon dioxide (amorphous)  
**Company;** Multisorb Technologies, Inc.  
**Street Address:** 325 Harlem Road  
**City, State, Zip, Country:** Buffalo, NY 14224-1893 USA  
**Telephone Number:** (716) 824 8900 [USA] Monday - Friday (8:00 - 5:00 EDT)  
**Fax Number:** (716) 824 4091 [USA]  
**Website / E-Mail :** multisorb.com

### Section 2 – Hazard Identification

**Emergency Overview:** An aluminum case containing a clear blue granular material that poses little or no immediate hazard. The case and the contents of the case are not combustible.

**Potential Health Effects:**

**Eyes:** None

**Skin:** None

**Ingestion:** Ingestion is very unlikely but if ingested get medical attention.

**Inhalation:** None

**Medical Effects Generally Aggravated by Exposure:** None

**Chronic Effects/Carcinogenicity:** None

### Section 3 – Composition / Information on Ingredients

Component Name	CAS Number	% by Weight
Synthetic amorphous silica gel (SiO <sub>2</sub> )	112926-00-8	80 - 90
Cobalt chloride	7646-79-9	.5
Aluminum	7429-90-5	10 - 20

While this material is not classified as hazardous under OSHA regulations, this MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

### Section 4 – First Aid Measures

**Eyes:** Rinse the eyes well with water while lifting the eye lids. If irritation persists, consult a physician.

**Skin:** Wash affected area with soap and water.

**Ingestion:** Ingestion is unlikely but if ingested get medical attention.

**Inhalation:** Remove the affected person to fresh air and get medical attention if necessary.

**Notes to Physician:** Not applicable

**Section 5 – Fire Fighting Measures**

**Flammable Properties:** Not flammable  
**Flash Point:** Not applicable **Method:** Not applicable  
**Flammable Limits:** Not flammable  
**Lower Flammability Limit:** Not applicable  
**Upper Flammability Limit:** Not applicable  
**Autoignition Temperature:** Not applicable  
**Hazardous Combustion Products:** Not applicable  
**Extinguishing Media:** Use extinguishing media that is appropriate for the surrounding fire. The silica gel and the aluminum case are not combustible.  
**Fire Fighting Instructions:** The silica gel and the aluminum case are not combustible.  
**Unusual Fire and Explosion Hazards:** None

**Section 6 – Accidental Release Measures**

**Spill:** Sweep or vacuum up and place the spilled material in a waste disposal container. Avoid raising dust. Wash with soap and water after handling.

**Section 7 – Handling and Storage**

**Handling:** Avoid raising dust and minimize the contact between worker and the material. Practice good hygienic work practices.  
**Storage:** Store in a cool, dry location. Keep in sealed containers away from moisture. The silica gel will readily adsorb moisture.

**Section 8 – Exposure Controls/Personal Protection**

**Engineering Controls:** Not required.  
**Respiratory Protection:** Not required.  
**Skin Protection:** Not required.  
**Eye Protection:** Not required.

<b>Exposure Limits</b>			
<b>Component Name</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>Other Recommended Limits</b>
Silica gel	TWA 20 mppcf (80 mg / m <sup>3</sup> % SiO <sub>2</sub> )	Not applicable	NIOSH REL TWA 6 mg / m <sup>3</sup> IDLH 3000 mg / m <sup>3</sup>
Cobalt chloride	.1 mg / m <sup>3</sup> (cobalt metal dust & fume)	TWA .02 mg / m <sup>3</sup> (as cobalt)	NIOSH REL TWA .05 mg / m <sup>3</sup> (Cobalt metal dust & fume as cobalt) IDLH 20 mg / m <sup>3</sup> (as metal dust & fume as cobalt)
Aluminum	TWA 15 mg / m <sup>3</sup> (total dust) TWA 5 mg / m <sup>3</sup> (respirable fraction)	1 mg / m <sup>3</sup> (respirable fraction of aerosol)	NIOSH REL TWA 10 mg / m <sup>3</sup> (total dust) TWA 5 mg / m <sup>3</sup> (respirable fraction)

**Section 9 – Physical and Chemical Properties**

<b>Appearance:</b>	Silver metal canister	<b>Vapor Density:</b>	Not applicable
<b>Odor:</b>	None	<b>Boiling Point:</b>	4046° F (2230° C) (Silica Gel)
<b>Physical State:</b>	Silver metal canister	<b>Melting Point:</b>	3110° F (1710° C) (Silica Gel)
<b>PH:</b>	Not applicable	<b>Solubility:</b>	Insoluble in water
<b>Vapor Pressure:</b>	Not applicable	<b>Specific Gravity:</b>	2.1

**Section 10 – Stability and Reactivity**

<b>Stability:</b>	Stable
<b>Conditions to avoid:</b>	Moisture and high humidity environments.
<b>Incompatibility:</b>	Water, fluorine, oxygen difluoride, chlorine trifluoride
<b>Hazardous Decomposition Products:</b>	None
<b>Hazardous Polymerization:</b>	Will not occur

**Section 11 – Toxicological Information**

This product and its components are not listed on the NTP or OSHA Carcinogen lists.

**Animal Toxicology** Tests for DOT Hazard classification  
( Tests Conducted on finely ground silica gel)

1 - hour LC<sub>50</sub> (rat) > 2 mg / l  
48 - hour oral LD<sub>50</sub> (rat) est. > 31,600 mg / kg  
48 - hour dermal LD<sub>50</sub> (rabbit) est. > 2,000 mg / kg  
Considered an ocular irritant

**IARC** Amorphous silica gel IARC - 3 (Unclassifiable as to Carcinogenicity in Humans)

**ACGIH** Cobalt and inorganic compounds, as Co are rated as A3 (confirmed animal carcinogen and unknown relevance to humans).

**IARC** Cobalt and cobalt compounds are rated as Group 2B (possible carcinogens to humans).

**Human Toxicology** Silica gel is a synthetic amorphous silica not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects. In the activated form, silica gel acts as a desiccant and can cause a drying irritation of the mucous membranes and skin in cases of severe exposure. Multisorb Technologies Inc. knows of no medical conditions that are abnormally aggravated by exposure to silica gel. The primary route of entry is inhalation of dust.

**Section 12 – Ecological Information**

Not known to have any adverse effect on the aquatic environment. Silica gel is insoluble and non-toxic.

**Section 13 – Disposal Information**

**Disposal Information** If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Materials of a hazardous nature that contact the product during normal use may be retained on the product. The user of the product must identify the hazards associated with the retained material in order to assess the waste disposal options. Dispose according to federal, state and local regulations.

**Section 14 – Transportation Information**

**U.S. Department of Transportation Shipping Name:** Not classified as a hazardous material. Not regulated.

**Section 15 – Regulatory Information** (Not meant to be all inclusive - selected regulations represented)

- TSCA Listed:** Yes (Ingredients)
- DSL/NDSL (Canadian) Listed:** Yes (Ingredients)
- OSHA:** See section 8 above.
- NIOSH:** See section 8 above.  
Animal tests conducted in 1976 - 1978. 18 month exposure at 15 mg / m<sup>3</sup> showed silica deposition in respiratory macrophages and lymph nodes, minimum lung impairment, no silicosis.
- ACGIH:** See section 8 above.
- DOT:** Not classified as a hazardous material.

**Section 16 – Other Information**

**HMIS – Hazardous Materials Identification System**

HMIS Rating	
Health	1
Flammability	0
Physical	0

The HMIS rating information is intended solely for the use of individuals trained in the use of the HMIS rating system.

The NPCA specifically recommends that preparers of MSDSs should not place HMIS PPE designation codes on the MSDSs or labels that leave the facility as it is not known the conditions under which the customer will use this product.

This MSDS was prepared by: George E. Mckedy  
Senior Applications Development Specialist  
Multisorb Technologies, Inc.

This data and recommendations presented in this data sheet concerning the use of our product and the materials contained therein are believed to be correct but does not purport to be all inclusive and shall be used only as a guide. However, the customer should determine the suitability of such materials for his purpose before adopting them on a commercial scale. Since the use of our products is beyond our control, no guarantee, expressed or implied, is made and no responsibility assumed for the use of this material or the results to be obtained therefrom. Information on this form is furnished for the purpose of compliance with Government Health and Safety Regulations and shall not be used for any other purposes. Moreover, the recommendations contained in this data sheet are not to be construed as a license to operate under, or a recommendation to infringe, any existing patents, nor should they be confused with state, municipal or insurance requirements, or with national safety codes.