



testo 316-1

Reliable gas leak detection



Detects gas leaks before it's too late!

ppm
CH₄



Flexible probe for hard to reach areas



Visual and audible alarm if limits are reached



TopSafe case protects from dirt and impact (optional)

Check for dangerous gas leaks before it's too late with the rugged and reliable **testo 316-1**. This light and compact meter is ideal for both installation and in-service spot-checks on all gas systems. It

quickly detects even the smallest gas leaks. No more guess work or soap bubbles. It's fast, accurate and professional gas leak detection. Adjust the sensitivity of the detector according to the locations

with the thumbwheel. A compact, flexible probe makes it easy to check those hard to reach places. A convenient TopSafe case protects the meter from dirt, moisture and impact.

We recommend: Qty. **Ordering Information** Part no.



Recommended kit		
Qty.	testo 316-1 gas leak detector with instruction manual and battery	0632.0316
	TopSafe, indestructible case with stand, protects from dirt, moisture and impact	0516.0189
	Case for safe storage of the testo 316-1 gas leak detector	0516.0182

Technical data for testo 316-1

Measuring range: 0 to 10,000 ppm CH₄

1st alarm limit: from 200 ppm CH₄

2nd alarm limit: 10,000 ppm CH₄

Alarm display: Visual with LED plus audible with buzzer

Lifetime: >5 hrs.

Dimensions: 7.5" x 2" x 2"

Weight: Approx. 11 ozs.

Warranty: 2 years

Ordering information

Qty.	Item	Part no.
	testo 316-1 gas leak detector with instruction manual and battery	0632.0316
	TopSafe, indestructible case with stand, protects from dirt, moisture and impact	0516.0189
	Case for safe storage of the testo 316-1 gas leak detector	0516.0182
	Plastic case for transport and storage of testo 316 and testo 315 (see below) incl. accessories	0516.3120
	Accessories set for testo 316-1 without TopSafe, with belt clip, carrying loop and probe holder	0554.0550

Safety & performance measurement for all

Monitor CO during boiler-tuning adjustments



Qty.	Item	Part no.
	testo 315-1 4-in-one instrument (CO, "H ₂ O, μA, °F) with instruction manual and battery	0632.0315
	Pressure set with flue draft probe	0554.3150
	Clamp probe for differential temperature measurement on pipes with max. diam. of 4.7"	0628.0031
	Test cables with alligator clips for measuring flame rod ionization current (2)	0554.0551
	testo infrared printer prints data with date, time and serial #	0554.0545
	TopSafe, indestructible case with stand, protects from dirt and impact	0516.0443
	Plastic case for transport and storage of testo 315-1 and testo 316-1 with accessories	0516.3120
<input type="checkbox"/>	Please send me more data on the testo 315-1/2	

testo Inc.
 35 Ironia Rd.
 Flanders, NJ 07836
 Phone: 800-227-0729
 Fax: 973-252-1729
 e-mail: info@testo.com
 www.testo.com