

# External Battery Pack



## Features

- Powers 115 V ac or 12 V dc products almost anywhere
- 3-digit battery status display
- Audible alarm signals overheat and under voltage conditions

Are you having trouble finding a power outlet? Hart' Scientific's 9320A external battery pack solves your problem. Plug your 115 VAC or 12 VDC powered calibration equipment into the 9320A for hours of useful operation. Don't get caught halfway through your work, only to find your battery pack just ran out of power. With the 3-digit battery status display on the front of the 9320A, you'll know how much time you're battery's got even before you start the job. The 9320A comes with an AC charger that recharges the battery pack from a standard wall outlet, and a DC charging cable to recharge the unit from the battery of a truck or car. What's more, you'll also get jumper cables, a handy light, and an air compressor too.

## Specifications

<b>AC Output</b>	115 ± 10 V ac RMS, 60 Hz ± 4 Hz
<b>Internal Battery Voltage (nominal)</b>	12 V dc
<b>DC Power Socket (maximum continuous load)</b>	12 A with automatic reset
<b>Fuse (internal)</b>	2 x 25 A or 1 x 50 A
<b>Internal Battery Type</b>	Sealed, AGM (absorbed glass mat) lead acid
<b>Internal Battery Capacity (minimum)</b>	20 Ah
<b>Internal Battery CCA Rating</b>	200 CCA
<b>Operating Temperature Range</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>Air Compressor Pressure</b>	250 PSI
<b>Nozzle Adapter (for air compressor)</b>	Two nozzle adapters, one sports needle adapter
<b>Size (HxWxD)</b>	24.1 cm x 40.8 cm x 20.3 cm (9.5 x 16 x 8 in)
<b>Weight</b>	10.5 kg (23 lb)