



Commercial Recovery Machine

FM3600-410A



Features

- Recovers ALL commonly used refrigerants, including R-410A (Puron™)
- 550PSI high pressure cut-off, high pressure gauges
- LED System status display
- Rugged and reliable
- Automatic shut-off when evacuation is completed

FM3600-410A Commercial Recovery Unit

For commercial refrigerant recovery applications, the FM3600-410A can recover vapor at up to two pounds per minute and can tolerate liquid directly through its compressor. Its large condenser ensures fast recovery in the hottest environments. A self-purging valve allows the condenser and tubing to purge without hose changes. The suction and discharge gauges and LED status display keep the technician informed during each recovery step.

| SPECIFICATIONS | |
|---------------------|---|
| Refrigerants | All refrigerants except R-11, R-113 and R-123 |
| Power Source | 115 VAC 50/60 Hz, 230 VAC 50/60 Hz, 10 VAC 50/60 Hz |
| Compressor | 0.5 HP high performance, oil less |
| Vacuum Rating | 13" Hg+ |
| High Pressure Limit | 550 PSI |
| Recovery Rate | .30 - 2.0 lbs./min. vapor 4.0 lbs./min. liquid |
| Auto 80% Shut-Off | Optional |
| Self Purging System | No hose changes |
| Weight | 35 lbs. |
| Dimensions | 12" x 13" x 7.5" |

| ORDERING INFORMATION | |
|----------------------|---|
| PART NUMBER | DESCRIPTION |
| 2000-3600 | FM3600-410A Commercial Recovery Machine |
| 2002-0081 | 80% Shut-Off Option |