

HT120 SERIES

High Temperature (120°C) Humidity Transmitter

The HT120 Series is a precision transmitter that provides quick and accurate humidity, barometric pressure, temperature, absolute pressure and dew point measurements in a wide range of applications. It has a wide temperature range of -40°C to 120°C and is resistant to most chemicals. This remote type transmitter comes standard with a 6 foot cable and is ideally suited for many different applications such as environmental chambers, compressed air, furnace and industrial applications. Many psychrometric units are selectable through the main menu. The unit is calibrated and adjusted to a traceable reference standard and each unit comes with a NIST certificate of calibration.



HT120	Humidity probe only - outputs: dew point, temperature and RH, three 0-10Vdc outputs, a RS232 (bi-directional), 24vdc power
HTP120	Humidity probe only - outputs: dew point, temperature and pressure, three 0-10Vdc outputs, a RS232 (bi-directional), 24vdc power
HTB120	Humidity probe only - outputs: dew point, temperature and barometric pressure, three 0-10Vdc outputs, a RS232 (bi-directional), 24Vdc power
HT120-DIS	Humidity probe with a 2 line backlit LCD display - outputs: dew point, temperature and RH, three 4-20mA outputs, a RS232 (bi-directional), two programmable alarm relays, 24Vdc power
HTP120-DIS	Humidity probe with a 2 line backlit LCD display - outputs dew point, temperature and pressure, three 4-20mA outputs, a RS232 (bi-directional), two programmable alarm relays, 24Vdc power
HTB120-DIS	Humidity probe with a 2 line backlit LCD display - outputs: dew point, temperature and barometric pressure, three 4-20mA outputs, a RS232 (bi-directional), 2 programmable alarm relays, 24Vdc power

