

OIL PUMPS

CHOOSING A GPI OIL PUMP

GPI Oil Pumps are specifically designed for use with high viscosity fluids. These weatherproof pumps will give you years of service. Consider the viscosity of the fluid being pumped and the temperature range when choosing the best oil

 PUMP SPECS				
	MODEL		P-200-2UR	
PART NUMBER	142100-03		118000-9	
VOLTAGE & TYPE	12-volt DC Aluminum Housing - Gerotor Gear		12-volt DC Molded Plastic Housing - Gear	
FLOWRATE	Up to 16 QPM (15 LPM)		Up to 8 GPM (30 LPM)	
DUTY CYCLE	30 min. On / 30 min. Off		30 min. On / 30 min. Off	
POWER CORD	Minimum Gauge: 10/3 (not supplied) Do not exceed 15 ft. of cord.		15 ft. (4.6m) of 10/3 cord.	
NOZZLE	3/4 in. Ball Valve Nozzle		1 in. Ball Valve Nozzle	
INLET/OUTLET SIZE	1 in. / 3/4 in.		1 in. / 1 in.	
SUCTION PIPE	Two-piece		Adjustable to 40 in.	
HOSE	8 ft. (2.5m) x 3/4 in.		12 ft. (3.7m) x 1 in.	
MOTOR PROTECTION	Requires a 50 amp automotive-type fuse. (not supplied)		25 amp Inline Fuse (supplied)	
UNIQUE FEATURE	Lightweight and suitable for waste oil.		Built-in handle with convenient Spin Collar for easy installation.	
USE WITH	Oil (up to 90W), waste oil, hydraulic fluid, antifreeze and non-flammable oil-based solvents.		Thin to medium lubricants up to 30W oil. Do not use with gasoline or diesel fuel.	
APPROVALS	Motor is U.L. Recognized Component and CSA Certified.		CSA Certified	
WARRANTY	1 Year		2 Year	