

The COD165 specifications are in the table below. Please find the attached product pricing information and image of the COD165. Please replace the COD125 with the COD165 for all future orders. Pricing for your region is enclosed. The COD165 webpage can be viewed at

<http://www.thermo.com/com/cda/product/detail/1,1055,16378,00.html>.

COD165 Specifications

<b>Samples :</b>	Up to 25 Digestion Tubes, 16mm diameter
<b>Selectable Temperatures :</b>	100 °C, 120 °C, 150 °C, 160 °C or 165 °C
<b>Selectable Times :</b>	30 minutes, 60 minutes, 120 minutes or continuous
<b>Safety Cover :</b>	Clear plastic, hinged to flip up for loading and unloading
<b>Reaching Set Temperature or End of Timed Cycle :</b>	Acoustic signal
<b>Thermoregulator :</b>	PID microprocessor
<b>Over-temperature Protection :</b>	Yes
<b>Precision :</b>	± 0.2 % end of scale
<b>Temperature Probe :</b>	Pt100 class A
<b>Temperature Probe Calibration :</b>	Automatic by software
<b>Heating Block Temperature Stability :</b>	±0.5 °C
<b>Heating Block Temperature Homogeneity :</b>	±0.5 °C
<b>Heating Block Temperature Precision :</b>	±1 °C
<b>Performance from 20 °C to 150 °C :</b>	12 minutes
<b>Power Supply :</b>	100 - 220 V, 50/60 Hz
<b>Power :</b>	400 W
<b>Weight :</b>	3.6 kg
<b>Dimensions (w x h x d) :</b>	155 mm x 95 mm x 275 mm