

Stability
±0.005°C



TU-20D

Stability
±0.005°C



TU-20HT

TU-20D Tempunit®

- A wider temperature range of -40°C* to 200°C
- Excellent temperature stability: ±0.005°C at 40°C
- 1.8kW heater power for fast heat up
- 4 digit setting with a bright LED digital temperature display
- This unit incorporates an RS232 connection
- User adjustable over-temperature cut-out
- Low liquid level cut-out as standard

TU-20HT Tempunit®

- This sophisticated Tempunit® covers a wide temperature range of -40°C* to 250°C
- Excellent temperature stability: ±0.005°C at 40°C
- 1.8kW heater power for fast heat up
- 4 digit setting with a bright LED digital temperature display
- RS232 connection supplied with TechneWorks software package and connecting lead as standard
- User adjustable over-temperature cut-out with an audible alarm fitted
- Low liquid level cut-out as standard

Technical Specification

Specifications to DIN 12876	TU-20D	TU-20HT
Temperature range*	-40°C to +200°C	-40°C to +250°C
Temperature selection	Digital	Digital
Temperature stability using water @ 40°C	±0.005°C	±0.005°C
Method of control	PID	PID
Temperature sensor	PRT	PRT
Adjustable over-temperature cut-out	Yes	Yes
Low liquid level cut-out	Yes	Yes
PC Interface	Yes RS232	Yes RS232
Heating/Pumping		
Pump capacity litres/minute	10	Internal circulation only
Pump capacity (mbar)	145	-
Nominal heater power at 120V (W)	1500	1500
Nominal heater power at 240V (W)	1800	1800
Cooling coil	No	Option
Extension below base (mm)	145	145
Dimensions L x W x H (mm)	237 x 124 x 260	237 x 124 x 260
Shipping Weight	4.0kg	4.0kg

* Refrigeration or cooling coil required for below ambient cooling (see Techne Flow and Dip Coolers and the cooling coil). The TU-20HT can only be used with the Dip Coolers

* Downloadable free of charge from www.techne.com

Ordering Information

Product Code	Description
FTU20DDC	TU-20D, advanced thermoregulator with RS232, -40°C to 200°C, (supplied with clamp)
FTU20HDC	TU-20HT, advanced high temperature thermoregulator with RS232 and TechneWorks software, -40°C to 250°C, (supplied with clamp)