



## IAM Controller

The optional IAM Controller allows the IAM system to be independent. Up to 16 IAM-100 can be connected to an IAM Controller, which in turn can build a pyramid type monitoring system.

Type	Central control system for up to 16 IAM-100	
	16 IAM Controller can be connected to one supervisory IAM Controller in a pyramid monitoring configuration	
Distance IAM-100	Up to 985 ft / 300 m from IAM Controller	
Power Supply	110 / 220 VAC; 60 / 50 Hz; 11 W	
Status Indicators	Green and red LEDs	
Audible Alarm	85 dB buzzer	
Relay	2 redundant alarm relays, SPDT	
	Rating 10 A @ 110 / 220 VAC, resistive load	
Ambient Conditions	Temperature	- 4 to +122 °F / - 20 to +50 °C
	Humidity	0 to 95 %RH, non condensing
Enclosure	Powder coated Aluminum, IP51	
Size (w x h x d)	approx. 10.3" x 10.4" x 3.3" / 265 x 265 x 85 mm	
Weight	approx. 5.7 lbs / 2.6 kg	
Approvals	CE, UL / CSA / IEC / EN 61010-1	

### World Headquarters

621 Hunt Valley Circle  
New Kensington, PA 15068, USA  
[www.MyBacharach.com](http://www.MyBacharach.com)

### Europe

Murco Ltd - a Bacharach company  
114a Georges Street Lower  
Dun Laoghaire, Co Dublin, Ireland

PHONE: +1 724-334-5000  
FAX: +1 724-334-5001  
E-MAIL: [help@MyBacharach.com](mailto:help@MyBacharach.com)