



Indoor Environmental Quality Monitor **IEQ Chek™**

IEQ Chek™ Features & Benefits:

- Versatile handheld instrument with flexible 7-sensor capacity
- Ideal for indoor environmental quality measurements
- On-board sensors for temperature and relative humidity; add up to 5 additional plug-and-play 'smart'
- · Large multi-line LCD graphic display
- · Stores over one million data points with SD flash card
- Optional data download kit with USB connection to PC and IQ Chek™ software



Multi-Sensor Flexibility

Bacharach's IEQ Chek™ is a versatile multi-sensor instrument for measuring, monitoring and recording indoor environments for air quality diagnosis. With its 7-sensor capacity, the new IEQ Chek™ measures temperature, relative humidity, and up to 5 additional plug-and-play 'smart' sensors, including carbon dioxide (CO₂), carbon monoxide (CO₁), oxygen (O₂), formaldehyde (HCHO), total volatile organic compounds (TVOCs), nitrogen dioxide (NO₂), sulfur dioxide (SO₂), ammonia (NH₃), hydrogen sulfide (H₂S) and combustible gases. Available with or without an on-board pump for sampling the air, the IEQ Chek™ has a large multi-line backlit LCD display with simultaneous viewing of all installed sensors, battery life, pump indicator and calibration status. Sophisticated, yet simple to use, the instrument has the capability to record and store over one million data points on a SD flash card with the option to download the data via USB connection to a PC using Bacharach's IQ™ Chek software.

Bacharach's IEQ Chek™ line offers maximum features, flexibility and functionality for indoor environmental quality monitoring, HVAC measurements, ASHRAE/ANSI compliance, process operations in non-hazardous environments and medical/lab applications. The IEQ Chek™ is an ideal tool for identifying energy saving opportunities in over-ventilated spaces, determining if carbon dioxide (CO₂) build-up is due to insufficient ventilation, pinpointing the presence of carbon monoxide generated from vehicles or appliances, and measuring other air contaminants such as formaldehyde or volatile organic compounds found in paints, chemicals or cleaning products.

IEQ Chek™ Specifications

Gases Detected: Carbon Dioxide (CO2), Carbon Monoxide (CO), Oxygen (O2), Formaldehyde (HCHO), Total Volatile Organic Compounds (TVOCs),

Nitrogen Dioxide (NO2), Nitric Oxide (NO), Sulfur Dioxide (SO2), Ammonia (NH3), Hydrogen Sulfide (H2S) and Combustible Gases

Non-Dispersive Infrared (NDIR), Electrochemical, Photoionization Detector (PID)

CO₂ CO2 CO₂ CO2 CO_2 02 0-5,000 0-10,000 0-5% vol 0-20% vol 0-100% 0-25% vol Range: vol maa mag 1% Resolution: 1 ppm 1 ppm 0.01% 0.01% 0.1% $\pm 2\%$ over range @ 68° F (20° C) / 1 bar pressure Accuracy: ±0.1% vol over range

Other Measurements:

Detection Principle:

Range:

Resolution:

Accuracy:

Temperature 23° F to 131° F (-5° C to 55° C) / 0.1° Resolution **Relative Humidity** 0-99.9% Non-Condensing / 0.1% Resolution

Dimensions: 7.75" L x 3.87" W x 3.06" D (19.7 cm x 9.8 cm x 7.8 cm)

Weight: 20 oz (567 g) including batteries Rugged ABS/Polycarbonate Housing:

Display: Large, Multi-line Backlit LCD Digital Display. Simultaneously Displays all Installed Sensors, Battery Life, Pump Indicator and

Calibration Progress Bar

80 dB Audible Alarm for One User-Selected Setpoint Alarm:

Operating Temperature Range: 41° F to 122° F (5° C to 50° C) **Operating Humidity Range:** 0 - 99% RH Non-Condensing

Data Storage: > 1 Million Data Points - Stored to SD Flash Card Optional USB Connection to PC w/ IQ Chek™ Software **Data Download:**

3 AA NiMH Rechargeable Batteries; (3 AA Alkaline Batteries can be User Installed); 6 VDC Power Adapter (N.Am. Plug or Intl. Pigtail Power:

w/IE320-C13 Socket)

12 to 14 Hours (Varies with Sensor Installation) **Run Time: Approvals:** CE Mark: IS EN61010-1:2001; EM/RFI EN 50270:2006 Warranty: Instrument - Two Years; CO2 Sensor - 1 Year

Instrument comes with 3 AA NiMH rechargeable batteries, charger/adapter, calibration adapter (pump versions only) and user manual **Kit Contents:**

IEQ Chek™ Part Number Configurator 15AB-CDEF

	Choose 1	Choose 1	Choose 1	Choose 1	Choose 1	Choose 1
5	Α	В	С	D	E	F
	0 = No sensor	0 = No sensor	0 = No sensor	0 = No sensor	0 = No sensor	0 = Do not use
	1 = CO ₂ (0-5,000 ppm)	1 = IR Combustible (0-5%)	1 = CO	1 = CO	1 = CO	1 = Diffusion, no DataLogging
	2 = CO ₂ (0-10,000 ppm)	2 = TVOC (0-300 ppm)	2 = 0 ₂	2 = 0 ₂	2 = 0 ₂	2 = Pump, no DataLogging
	3 = CO ₂ (0-5% vol)	3 = TVOC (0-50 ppm)	3 = NH ₃	3 = NO ₂	3 = \$02	3 = Diffusion w/ DataLogging
	4 = CO ₂ (0-20%)		4 = NO	4 = HCHO	4 = H ₂ S	4 = Pump w/ DataLogging
	5 = CO ₂ (0-100% vol)					5 = Diffusion, no DL, ext. battery
	5	5 A 0 = No sensor 1 = CO ₂ (0-5,000 ppm) 2 = CO ₂ (0-10,000 ppm) 3 = CO ₂ (0-5% vol) 4 = CO ₂ (0-20%) 5 = CO ₂	5 A B 0 = No sensor 0 = No sensor 1 = CO ₂ (0-5,000 Combustible (0-5%) 2 = CO ₂ (0-10,000 Combustible (0-5%) 3 = CO ₂ (0-5% vol) 4 = CO ₂ (0-20%) 5 = CO ₂	5 A B C 0 = No sensor 0 = No sensor 0 = No sensor 1 = CO ₂ (0-5,000 combustible ppm) (0-5%) 1 = CO 2 = CO ₂ (0-10,000 ppm) ppm) 2 = TVOC (0-300 ppm) ppm) 3 = CO ₂ (0-5% vol) (0-50 ppm) 3 = TVOC (0-50 ppm) 4 = CO ₂ (0-20%) 4 = NO 5 = CO ₂ 5 = CO ₂	5 A B C D 0 = No sensor 1 = CO ₂ (0-5,000 combustible ppm) 1 = IR CO 1 = CO 1 = CO 2 = CO ₂ (0-10,000 ppm) 2 = TVOC (0-300 ppm) 2 = O ₂ 2 = O ₂ 3 = CO ₂ (0-5% vol) 3 = TVOC (0-50 ppm) 3 = NH ₃ 3 = NO ₂ 4 = CO ₂ (0-20%) 4 = NO 4 = HCHO 5 = CO ₂ 5 = CO ₂ 5 = CO ₂	5 A B C D E 0 = No sensor 1 = CO ₂ (0-5,000 combustible ppm) 1 = IR CO 1 = CO 1 = CO 1 = CO 2 = CO ₂ (0-10,000 ppm) 2 = TVOC (0-300 ppm) 2 = O ₂ 2 = O ₂ 2 = O ₂ 3 = CO ₂ (0-5% vol) 3 = TVOC (0-50 ppm) 3 = NH ₃ 3 = NO ₂ 3 = SO ₂ 4 = CO ₂ (0-20%) 4 = NO 4 = HCHO 4 = H2S 5 = CO ₂ 5 = CO ₂ 5 = CO ₂ 5 = CO ₂

6 = Pump, no DL, ext. battery

7 = Diffusion w/ DL, ext. battery

8 = Pump wDL, extended battery

IEQ Chek™ Common Configurations

*All configurations include Temp and RH 1510-0002 CO₂ (0-5,000 ppm), Pump

1510-0004 CO₂ (0-5,000 ppm), Pump, DataLogging 1510-1001 CO₂ (0-5,000 ppm), CO, Diffusion

1510-1002 CO₂ (0-5,000 ppm), CO, Pump

1510-1003 CO₂ (0-5,000 ppm), CO, Diffusion, DataLogging 1510-1004 CO₂ (0-5,000 ppm), CO, Pump, DataLogging

1510-1302 CO2 (0-5,000 ppm), CO, NO2, Pump 1510-1304 CO₂ (0-5,000 ppm), CO, NO₂, Pump, DataLogging

1510-1403 CO₂ (0-5,000 ppm), CO, HCHO, Diffusion,

DataLogging

1512-1008 CO₂ (0-5,000 ppm), TVOC (0-300ppm), CO, Pump, Ext. Battery, DataLogging

1520-0002 CO₂ (0-10,000 ppm), Pump

1520-0003 CO₂ (0-10,000 ppm), Diffusion, DataLogging

1530-0001 CO₂ (0-5%), Diffusion 1540-0002 CO2 (0-20%), Pump

Accessories & Replacement Parts

1509-0001 IQ Chek™ DataLogging Option (Includes

2GB flash card, cable, software & SD card reader)

1509-0002 Rugged Transport Case for IEQ Chek™

1509-0003 10" probe w/30" of sample hose for IEQ Chek™ **1509-0005** IEQ Chek™ Externally-mounted, NiMH Battery Pack

(required when CO2 / TVOC sensors are installed in the same instrument)

1509-0008 IEQ Chek™ Replacement NiMH Batteries (pkg. of 3)

BACHARACH

Distributed By:



