



Badger Meter

Mechanical Scalable Transmitters

Models PM5 and MS-E5XP

DESCRIPTION

The PM5 and MS-E5XP models are pulse transmitters designed to be used with Badger Meter® magnetic drive meters. The pulse transmitter provides a scaled electrical pulse signal (switch closure type) for each discrete unit of liquid volume metered. The signal is used to operate instruments and controls.

These transmitters are identical except for the housing. The PM5 transmitter has a glass filled plastic housing and a NEMA 4X rating. The MS-E5XP housing is bronze with a NEMA 4 rating.

The transmitters are available in a wide range of gear ratios and pulse rates up to 1500 contact closures per minute.

OPERATION

The flow of liquid through the meter is measured by a disc or piston metering element. The motion of the measuring element is transferred to a magnetic coupling. One of these magnets is in the measuring chamber, the other in the transmitter.

The driven magnet (inside the transmitter) then rotates a gear train and pulse magnet. As the pulse magnet turns, it causes the reed switch to open and close. Contact closures from the switch are transmitted to a remote instrument or counter which records the quantity of flow.

APPLICATIONS

These transmitters are used in metering systems that require pulse closures for recording rate of flow, quantity of flow, liquid feeding, blending and batching.

FEATURES

- MS-E5XP transmitter is explosion-proof with CSA listing for Class 1, Group D, Division I (Hazardous Locations)
- Does not require external power
- Rugged, cast bronze housing (MS-E5XP only)
- Corrosion resistant, glass filled plastic enclosure (PM5 only)
- High temperature rating: 250° F (121° C)
- Watertight NEMA 4 (bronze) or NEMA 4X (plastic) housing
- Hermetically sealed reed switch output




MS-E5XP (rear) and PM5 Transmitters

SPECIFICATIONS

Switch Rating	1A, 50V DC and 0.28A, 180V DC general use 0.7A, 35V AC and 0.28A, 125V AC general use
Reed Switch	Single-pole, single-throw
Duty Cycle	Approximately 50%
Operating Temperature	250° F (121° C), maximum.
Weight	Bronze: 5 lb (2.3 kg), plastic: 2 lb (0.9 kg)

WIRING DIAGRAM



NOTE: The green wire is a ground wire and is found only on the MS-E5XP.

Control. Manage. Optimize.

Trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2014 Badger Meter, Inc. All rights reserved.

www.badgermeter.com

The Americas | Badger Meter | 4545 West Brown Deer Rd | PO Box 245036 | Milwaukee, WI 53224-9536 | 800-876-3837 | 414-355-0400
México | Badger Meter de las Americas, S.A. de C.V. | Pedro Luis Ogazón N°32 | Esq. Angelina N°24 | Colonia Guadalupe Inn | CP 01050 | México, DF | México | +52-55-5662-0882
Europe, Middle East and Africa | Badger Meter Europa GmbH | Nurtinger Str 76 | 72639 Neuffen | Germany | +49-7025-9208-0
Europe, Middle East Branch Office | Badger Meter Europe | PO Box 341442 | Dubai Silicon Oasis, Head Quarter Building, Wing C, Office #C209 | Dubai / UAE | +971-4-371 2503
Czech Republic | Badger Meter Czech Republic s.r.o. | Maříkova 2082/26 | 621 00 Brno, Czech Republic | +420-5-41420411
Slovakia | Badger Meter Slovakia s.r.o. | Racianska 109/B | 831 02 Bratislava, Slovakia | +421-2-44 63 83 01
Asia Pacific | Badger Meter | 80 Marine Parade Rd | 21-06 Parkway Parade | Singapore 449269 | +65-63464836
China | Badger Meter | 7-1202 | 99 Hangzhong Road | Minhang District | Shanghai | China 201101 | +86-21-5763 5412