

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.3

Revision Date: 26.03.2003

## DOW CORNING(R) 210H FLUID, 100 CS.

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Trade name : DOW CORNING(R) 210H FLUID, 100 CS.

**Company** : Dow Corning S.A.

Parc Industriel - Zone C

B-7180 Seneffe Belgium

Service : Dow Corning Central Europe Tel: +49 6112371

Fax: +49 611237609

Dow Corning Northern Europe Tel: +44 1676528000

Fax: +44 1676528001

Dow Corning Southern Europe Tel: +33 472841360

Fax: +33 472841379 Tel: +44 1446732350

**Emergency Phone Number** : Dow Corning (Barry U.K. 24h)

Dow Corning (Wiesbaden 24h)

Tel: +49 61122158

Dow Corning (Seneffe 24h)

Tel: +32 64 888240

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone

**Hazardous Ingredients:** 

Name CAS-No. EINECS/ Conc. (% w/w) Classification

ELINCS No.

No hazardous ingredients.

#### 3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

#### 4. FIRST AID MEASURES

On contact with eyes : No first aid should be needed.

On skin contact : No first aid should be needed.

If inhaled : No first aid should be needed.

On ingestion : No first aid should be needed.

#### 5. FIRE FIGHTING MEASURES



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.3

Revision Date: 26.03.2003

# DOW CORNING(R) 210H FLUID, 100 CS.

Suitable extinguishing media : Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire

exposed containers.

**Unsuitable extinguishing** 

media

None known.

**Hazards during fire fighting**: None known.

Special protective equipment/procedures

A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate

the area according to your local emergency plan.

**Hazardous Combustion** 

**Products** 

Silica. Carbon oxides and traces of incompletely burned carbon compounds.

Formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions** : Wear proper protective equipment.

Precautions to protect the

environment

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or

other appropriate barriers.

**Methods for cleaning up** : Determine the need to evacuate or isolate the area according to your local emergency

plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product

produces an extremely slippery surface.

#### 7. HANDLING AND STORAGE

Advice on safe handling : Avoid eye contact. General ventilation is recommended.

**Advice on storage** : Do not store with oxidizing agents.

**Specific uses** : Refer to technical data sheet available on request.

Unsuitable packaging

materials

: None known.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls** : Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name CAS-No. Exposure Limits

None of the components have assigned exposure limits.

2 of 6



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.3

Revision Date: 26.03.2003

# DOW CORNING(R) 210H FLUID, 100 CS.

Personal protection equipment

**Respiratory protection** : Respiratory protection is not normally required.

**Hand protection** : Gloves are not normally required.

**Eye protection** : Safety glasses should be worn.

**Skin protection** : Protective equipment is not normally necessary.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

**Environmental exposure** 

controls

Refer to section 6 and 12.

**Additional information**: These precautions are for room temperature handling. Use at elevated temperature or

aerosol/spray applications may require added precautions. For further information regarding the use of silicones in consumer aerosol applications, please refer to the guidance document regarding the use of silicone-based materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or

contact the Dow Corning customer service group.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Form: Liquid Colour: Brown Odour: Very little

Other data

**Boiling point/range** : > 35C/95F

Flash point : > 175 °C (Closed Cup)

**Explosive properties** : No

**Specific Gravity** : 0.97

Viscosity : 100 cSt at 25°C.

Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

#### 10. STABILITY AND REACTIVITY

**Stability** : Stable under normal usage conditions.

**Conditions to avoid** : None established.

Materials to avoid : Can react with strong oxidising agents.

3 of 6



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.3

Revision Date: 26.03.2003

## DOW CORNING(R) 210H FLUID, 100 CS.

**Hazardous decomposition** 

products

See section 11.

#### 11. TOXICOLOGICAL INFORMATION

On contact with eyes : May cause temporary discomfort.

On skin contact : No adverse effects are normally expected.

**If inhaled** : No adverse effects are normally expected.

On ingestion : No adverse effects are normally expected.

**Other Health Hazard** 

**Information** 

Product may emit formaldehyde vapours at temperatures above 150°C in the presence of

air. Formaldehyde vapour is harmful by inhalation and irritating to eyes and respiratory

system at breathing concentration less than one part per million (1 ppm).

- Based on product test data.
- <sup>2</sup> Based on test data from similar products.
- This information is based either on test data, extrapolation from tests on similar materials, review of component data, or a combination of these sources.

#### 12. ECOLOGICAL INFORMATION

#### **Environmental fate and distribution**

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

#### **Ecotoxicity effects**

No adverse effects on aquatic organisms.

**Bioaccumulation** : No bioaccumulation potential.

#### Fate and effects in waste water treatment plants

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

## Additional environmental information

Additional environmental information on the silicone component is available on request.

#### 13. DISPOSAL CONSIDERATIONS

**Product disposal** : Dispose of in accordance with local regulations.

**Packaging disposal** : Dispose of in accordance with local regulations.



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.3

Revision Date: 26.03.2003

# DOW CORNING(R) 210H FLUID, 100 CS.

#### 14. TRANSPORT INFORMATION

#### Road / Rail (ADR/RID)

Not subject to ADR/RID.

#### Sea transport (IMDG)

Not subject to IMDG code.

#### Air transport (IATA)

Not subject to IATA regulations.

## 15. REGULATORY INFORMATION

## **Labelling according to EEC Directive**

No special packaging or labelling requirements.

#### National legislation / regulations

**Ozone depleting** 

chemicals

: No ozone depleting chemicals are present or used in manufacture.

**Status** 

**EINECS** : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.3

Revision Date: 26.03.2003

## DOW CORNING(R) 210H FLUID, 100 CS.

#### 16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.