

# Field dry-wells and furnaces



Fluke Calibration dry-wells interface directly to the Fluke 754 for fully automated calibration.



## Fluke Calibration 9103, 9140 and 9141 Field Dry-Wells and 9150 Thermocouple Furnace

Temperature sensor test and calibration

- Lightweight and very portable
- Accuracy to  $\pm 0.25\text{ }^{\circ}\text{C}$
- RS-232 and Interface-it software included
- Interchangeable inserts
- 9103 goes as low as  $-25\text{ }^{\circ}\text{C}$ .
- 9140 is 6 pounds (2.7 kg) and 9141 is 3.6 kg (8 pounds)
- 9140 and 9141 reach max temp in 12 minutes
- 9150 extends up to  $1200\text{ }^{\circ}\text{C}$  covering a wide range of T/C types.
- Direct interface to Fluke 754

**Recommended accessories:** carrying case, additional inserts, reference temperature sensor and indicator

Each dry-well includes one of four available well inserts, an optional carrying case, RS-232 interface, instrument control software and a MIST-traceable calibration.

## Ordering information

**9103** Dry-Well,  $-25\text{ }^{\circ}\text{C}$  to  $140\text{ }^{\circ}\text{C}$

**9140** Dry-Well,  $35\text{ }^{\circ}\text{C}$  to  $350\text{ }^{\circ}\text{C}$

**9141** Dry-Well,  $50\text{ }^{\circ}\text{C}$  to  $650\text{ }^{\circ}\text{C}$

**9150** Thermocouple Furnace,  $150\text{ }^{\circ}\text{C}$  to  $1200\text{ }^{\circ}\text{C}$

**9316** Rugged Carrying Case for 9103

**9308** Rugged Carrying Case for 9140

**9309** Rugged Carrying Case for 9141

**9315** Rugged Carrying Case for 9150

**2514** Dry-Well Interface Cable to Fluke 744

Insert (interchangeable). Specify "A", "B", "C", "D"

## 9103, 9140, 9141 and 9150 Insert Options

