

CPT6010 Digital Pressure Transducer

Data Sheet CPT6010 • 04/2015

Applications

- High accuracy transfer standard
- Pressure standard in test & calibration stands
- Wind tunnels
- Hydrology, Oceanography
- Aerospace, Metrology

Features

- 0.020% FS accuracy
- Ranges:
Absolute: 0-7.5 psia to 0-6000 psia
Gauge: 0-5 psig to 0-6000 psig
- Pneumatic or Hydraulic
- RS-232 or RS-485 communication
- 303 stainless steel housing



Digital Pressure Transducer Model CPT6010

Description

General

The CPT6010 Digital Pressure Transducer is a self-contained pressure sensing device that provides high accuracy pressure measurements in both the single and dual calibration models. This transducer incorporates a low hysteresis silicon sensor with electronically compensated pressure linearity over the specified temperature range.

The CPT6010 Transducer is characterized over the full pressure and temperature range to achieve 0.020% FS uncertainty. This uncertainty specification includes linearity, hysteresis, repeatability and temperature errors. Also featured is an output which is updated at a rate of 50 readings per second (20 ms).

Applications

The CPT6010 is used in OEM Applications where a high accuracy pressure sensing is required. It can also be used as a

transfer standard or in pressure calibration and testing areas of production facilities.

Functional Flexibility

The CPT6010 Digital Pressure Transducer is a high accuracy pressure measurement component that uses either RS-232 or RS-485 to communicate with a host computer over long distances. Any MS-DOS compatible PC with an available serial output port can serve as the host controller.

System designers will appreciate the flexibility offered by having highly accurate pressure transducers that are not tied to a front panel and which may be located remotely. For remote operation the transducer equipped with RS-485 can be located up to 4,000 feet from the host. A simple cable can accommodate both the power and the two-way communications requirements.

Specifications

Total Uncertainty	0.020%FS. Total uncertainty (k=2) includes hysteresis, linearity, repeatability, reference standard, drift and temperature effects over the calibrated range for the calibration interval specified with periodic re-zeroing.
Calibration Stability after warmup	Less than 0.02% FS for six months.
Calibration	Calibration Interval: 180 days Cal Uncertainties: 0.020% FS Calibration adjustment: Zero and Span. (Zero and span may be reset via the serial interface without affecting the linearity.)
Pressure Ranges	Abs: 0-7.5 psia up to 0-6000 psia. Gauge: 0-5 psig up to 0-6000 psig.
Special Pressure Ranges	Vacuum or bidirectional ranges. Metric pressure units also available.
Pressure Units	Selected from a list of 35: psi, inHg @0°C and 60°F, inH ₂ O @4°C, 20°C and 60°F, ftH ₂ O @ 4°C, 20°C and 60°F, mTorr, inSW @ 0C, ftSW @ 0C, ATM, bars, mbars, mmH ₂ O @ 4°C, cm H ₂ O @ 4°C, MH ₂ O @ 4°C, mmHg @ 0°C, cmHg @ 0°C, Torr, hPa, mPa, kPa, Pa, D/cmsq, G/cmsq, Kg/cmsq, mSW @ 0°C, OSi, PSF, TSF, TSI, μHg @ 0°C, %fs. All seawater units are 3.5% salinity.
Resolution	Up to 1 ppm, depending on measurement units and range.
Overpressure Limit	150% FS or greater, depending on range
Compensated Temp. Range	15 to 45 °C
Warm-up	10 minutes to rated accuracy
Reading Rate	50 Hz
Communications	RS-232 or RS-485. LabVIEW ^{®1} drivers are available.
Max. Transmission	4000 feet (RS-485)
Multi-drop Capacity	The maximum number of RS-485 Series 6000 transducers which can be connected to a single host computer is 31.

Mechanical Shock	5g max.
Case Size	1.75" wide x 6.0" long (4.45 x 15.24 cm), not including pneumatic and electrical.
Weight	Approximately 12 ounces (28.3 grams).
Media Compatibility	All media compatible with 316L stainless steel.
Fittings	Pressure Port: 1/4 inch male NPT Reference Port: 1/16 inch barb (gauge instruments only)
Power	9-18 VDC, 45mA @ 12 VDC 6 pin Bendix connector #PT02E-10-6P
Compliance	Conforms to CE standards EN 50081-1, EN 50082-1, EN 50081-2, and EN 50082-2.
Options	Relief Valves —up to 1000 psig Custom ranges.

¹LabVIEW[®] is a trademark of National Instruments Corporation.

The calibration program at Mensor is accredited by A2LA as complying with both the ISO/IEC 17025:2005 and the ANSI/NCSL Z540-1-1994 standards. All Mensor primary standards are traceable to NIST. Mensor is registered to ISO9001:2008.



Since product innovation is a continuous process at Mensor, we reserve the right to change specifications without notice.

Represented by:



Mensor
201 Barnes Drive
San Marcos, Texas 78666
Toll Free: 800-984-4200
Tel: 512-396-4200
Fax: 512-396-1820
Email: sales@mensor.com