

## PUR-2W-M12 Pura Transmitter

- Below are the NEW (after 1st July 2025) & OLD (before 1st July 2025) product ordering codes
- Compare the two ordering code systems and you will see only 40% of the ordering code has changed
- We intentionally left the product description unchanged to ensure you can quickly cross check the NEW & OLD product specifications
- If you want to understand more about this change, then read the "Customer Explanation" which is included below

### NEW

Product Parent Code: PUR-2W-M12 Pura Transmitter M12 2-wire 4-20mA		
Base Model		
Pura M12 Transmitter 2-wire 4-20 mA	PUR-2W-M12	
PRM - Double Bagged		A
OEM - Single Bagged		B
SEN - Sensor only, no block		C
Range		
-120 to -40°C (-184 to -40°F) dp range		A
Non-standard measurement range: v = zero value, w = full scale value, x = unit (C = °Cdp, F=°Fdp, P=ppmV) y = Pressure for ppmV conversion in bar/psi, z = pressure unit (PG=psig, PA=psia, BG=barg, BA=bara) blank = 0 barg/psig) e.g. 0-100ppm @ 10barg = 0/100P-10BG		R
Ordering Example		
PUR-2W-M12-AA	Pura Transmitter M12 2 wire 4-20mA, Double Bagged, with -120 to 40 °C range.	

### OLD

Product Parent Code: PUR-TX-2W-M12 Pura Transmitter 2-wire 4-20 mA								
Product Ordering Code {Feature A}+{Feature B}+{Feature C}								
Feature	Item	Description						
Feature {A}	Base Model	PUR-TX-2W-M12 Pura M12 Transmitter 2-wire 4-20 mA						
Feature {B}	Version	<table border="1"> <tr> <td>PRM</td><td>Double bagged</td></tr> <tr> <td>OEM</td><td>Single bagged</td></tr> <tr> <td>SEN</td><td>Sensor only, no block</td></tr> </table>	PRM	Double bagged	OEM	Single bagged	SEN	Sensor only, no block
PRM	Double bagged							
OEM	Single bagged							
SEN	Sensor only, no block							
Feature {C}	Range	<table border="1"> <tr> <td>(-120/-40)</td><td>-120 to -40°C (-184 to -40°F) dp range</td></tr> <tr> <td>(v/wx-yz)</td><td>Non-standard measurement range: v = zero value, w = full scale value, x = unit (C = °Cdp, F=°Fdp, P=ppmV) y = Pressure for ppmV conversion in bar/psi, z = pressure unit (PG=psig, PA=psia, BG=barg, BA=bara) blank = 0 barg/psig) e.g. 0-100ppm @ 10barg = 0/100P-10BG</td></tr> </table>	(-120/-40)	-120 to -40°C (-184 to -40°F) dp range	(v/wx-yz)	Non-standard measurement range: v = zero value, w = full scale value, x = unit (C = °Cdp, F=°Fdp, P=ppmV) y = Pressure for ppmV conversion in bar/psi, z = pressure unit (PG=psig, PA=psia, BG=barg, BA=bara) blank = 0 barg/psig) e.g. 0-100ppm @ 10barg = 0/100P-10BG		
(-120/-40)	-120 to -40°C (-184 to -40°F) dp range							
(v/wx-yz)	Non-standard measurement range: v = zero value, w = full scale value, x = unit (C = °Cdp, F=°Fdp, P=ppmV) y = Pressure for ppmV conversion in bar/psi, z = pressure unit (PG=psig, PA=psia, BG=barg, BA=bara) blank = 0 barg/psig) e.g. 0-100ppm @ 10barg = 0/100P-10BG							

**Dear Customers,**

On 1<sup>st</sup> July 2025, the ordering code part number string on all Michell Instruments Dew-Point Sensors was changed. The new system will be used on shipments from Michell Instruments Ltd (UK) from 8<sup>th</sup> July and will be visible to yourselves shortly after this date.

We acknowledge there could be a temporary impact, as you amend your ordering information for sending purchase orders to us. This note should explain what the changes are and why we have changed order codes that have been in place since 2008 onwards.

### **What has changed?**

Our product ordering code has been made up of three elements:


- Product Parent Code: Example EA2-TX (90% of these codes will be unchanged).
- Product Part Number String: Example -100/+20°C ... 100% of these strings will transfer to letters, confirming exact product specifications.
- Product Description: No change, to allow for simple cross referencing.

### **Reasons for the Change and the Resulting Benefits**

Update in overall technology, designed as a Configured BOM system, left us with a semi-automated system, restricting access to the following benefits:

- Further delivery improvements
- Further reductions in low level quality escapes
- New data handling technology (NEW Online Calibration Certificate download option for dew-point sensors, which can be [viewed here](#))

The reasons listed above demonstrate a seamless 100% automated process from quotation to shipment, as illustrated below.



### **Summary**

We appreciate that 40% of the order code system has changed, **so we have taken the following steps to assist with your transition:**

- All Global Customer Service Departments (CSD) are trained to assist with questions
- OLD v NEW Order Code comparison can be found on the product pages on our website.
- New-style order code sheets are available on every product page (**Easidew Transmitter EA2 – Order Codes, [view here](#)**)

- The global PST Sales Team has been trained on the new ordering code system

We hope this has been informative and expect the new order code system to have bedded in within 3 to 4 weeks.

Peter Shepherd - Group Product Manager – Dew-Point Sensors