

DESCRIPTION

The RVL liquid flow meter uses vortex-shedding technology with embedded piezoelectric pressure sensors. The meter has no moving parts, and any potential for fluid contamination is eliminated by the non-metallic corrosion-resistant body materials. The meter includes a compact plug-in transmitter module with two-wire 4...20 mA or three-wire pulse output. All electronics are housed in a corrosion-resistant enclosure. Units can be recalibrated and reprogrammed in the field.


APPLICATION

The RVL is perfect for aggressive or easily contaminated fluids.

- Ultra-pure water distribution
- RO/DI skids
- Cooling water
- Chemical injection
- Nonabrasive slurries

OPERATING PRINCIPLE

Operation of the RVL vortex flow meter is based on the vortex shedding principle. As fluid moves around a strut, vortices (eddies) are formed and move downstream. They form alternately, from one side to the other, causing pressure fluctuations that are sensed by a piezoelectric crystal in the sensor tube. The frequency of the vortices is directly proportional to the flow rate.




CONSTRUCTION

The precision machined bodies provide quality end fittings, while avoiding ionic contamination. There are no metallic wetted parts, gaskets or elastomers in the meter. The body material selected is homogeneous throughout the flow path.



OPTIONAL SOFTWARE

An optional software utility kit is available to configure the RVL 4...20 mA output. (The pulse output is not field configurable.) Part number RVS220-954 contains a RS232 nine-pin cable, software CD, TTL to RS232 converter and a board interface cable. The program enables easy configuration of span, damping and units of measurement.



MATERIAL SELECTION

When choosing the best flow meter for a process, review the concentration, operating temperatures and operating pressure of the fluid being measured. In a thermoplastic piping system, choose the same material for the meter and the pipe wherever possible to maintain fluid compatibility and aid in bonding the materials. The table below shows the compatibility of fluid types with thermoplastic materials.

Chemical	PVC	PVDF	CPVC	Polypropylene
Aluminum Hydroxide	A	A	A	A
Chlorine Water	A	B	A	D
Fuel Oils	A	B	—	A
Hydraulic Oil	A	A	—	D
Hydrochloric Acid 37%	B	A	A	C
Hydrochloric Acid 20%	B	A	C	A
Isopropyl Alcohol	A	—	C	A
Nitric Acid (Concentrated)	B	A	D	D
Phosphoric Acid (>40%)	B	B	A	A
Potassium Hydroxide	A	A	A	A
Propylene Glycol	C	—	C	A
Sulfuric Acid (10...75%)	A	A	A	A
A= Excellent B= Good C= Fair D= Severe effect				

FLUID CONSIDERATIONS

In vortex flow meters, fluids with high viscosities tend to dampen the formation of vortices and reduce the effective range. Viscosities above 1 cSt raise the minimum readable flow rate, reducing rangeability. The effect is linear to viscosity. Particles and internal bubbles do not usually affect vortex meters. In slurry services, PVDF models typically work very well. Slurries containing grit can wear down the bluff body over a period of time and long fibers can catch and build up on the bluff, decreasing accuracy.

Liquids with specific gravities higher than 2.0 adversely affect the permissible amount and duration of over-flow range.

Reduction of Range Based on Viscosity			
Viscosity	Minimum	Maximum	Flow Range
1 cSt	1	12	12:1
2 cSt	2	12	6:1
3 cSt	3	12	4:1
4 cSt	4	12	3:1
5 cSt	5	12	2.4:1
6 cSt	6	12	2:1

Meters are calibrated with tap water at 1 cSt (32 SSU) at ambient temperature

SPECIFICATIONS

Measured Fluids	Liquids
Connections	Butt or NPT thread Wafer (mounted between flanges)
Accuracy	±1% of full scale, 4...20 mA; ±2% of full scale, frequency pulse
Repeatability	±0.25% actual flow
Response Time	2 seconds minimum, step change in flow
Input Power	13...30V DC
Signal Output	4...20 mA or frequency pulse (source-sink driver; 1A source/1.5A sink; typical output resistance 10 Ω)
Enclosure	NEMA 4X (IP 66)
Certifications	CE: EN50082-1:1992

Pressure vs Temperature Ratings

NPT/Butt End Fittings

Maximum Fluid Temperature	Maximum Operating Pressure		
	PVC	CPVC	PVDF
203° F (95° C)*	—	24 psig (1.6 bar)	40 psig (2.7 bar)
150° F (66° C)	—	63 psig (4.3 bar)	130 psig (8.9 bar)
100° F (38° C)	93 psig (6.4 bar)	120 psig (8.3 bar)	150 psig (10.3 bar)
70° F (21° C)	150 psig (10.3 bar)	150 psig (10.3 bar)	150 psig (10.3 bar)

*Reduces low flow rate on 1/4 in. (6 mm) meter

Wafer End Fittings

Maximum Fluid Temperature	Maximum Operating Pressure			
	PVC	PP	CPVC	PVDF
203° F (95° C)	—	—	24 psig (1.6 bar)	40 psig (2.7 bar)
150° F (66° C)	—	90 psig (6.2 bar)	100 psig (6.9 bar)	130 psig (8.9 bar)
100° F (38° C)	130 psig (8.9 bar)	130 psig (8.9 bar)	130 psig (8.9 bar)	150 psig (10.3 bar)
70° F (21° C)	150 psig (10.3 bar)	150 psig (10.3 bar)	150 psig (10.3 bar)	150 psig (10.3 bar)

FLOW RANGES

NPT/Butt End Fittings


Meter Size	Minimum Flow	Maximum Flow	Turndown Ratio
1/4 in. (6.3 mm)	0.6 gpm (2.3 lpm)	5 gpm (19 lpm)	8:1
1/2 in. (12.7 mm)	1.5 gpm (5.7 lpm)	15 gpm (56.8 lpm)	10:1
3/4 in. (19.1 mm)	2.5 gpm (9.5 lpm)	25 gpm (94.6 lpm)	10:1
1 in. (25.4 mm)	5.0 gpm (18.9 lpm)	50 gpm (189 lpm)	10:1
1-1/2 in. (38.1 mm)	10.0 gpm (37.9 lpm)	100 gpm (379 lpm)	10:1
2 in. (50.8 mm)	20.0 gpm (75.7 lpm)	200 gpm (757 lpm)	10:1

Wafer End Fittings

Meter Size	Minimum Flow	Maximum Flow	Turndown Ratio
1/2 in. (12.7 mm)	1.5 gpm (5.7 lpm)	15 gpm (56.8 lpm)	10:1
3/4 in. (19.1 mm)	2.5 gpm (9.5 lpm)	25 gpm (94.6 lpm)	10:1
1 in. (25.4 mm)	5.0 gpm (18.9 lpm)	50 gpm (189 lpm)	10:1
1-1/2 in. (38.1 mm)	10.0 gpm (37.9 lpm)	100 gpm (379 lpm)	10:1
2 in. (50.8 mm)	20.0 gpm (75.7 lpm)	200 gpm (757 lpm)	10:1
3 in. (76.2 mm)	30.0 gpm (113.6 lpm)	300 gpm (1136 lpm)	10:1


DIMENSIONS

NPT/Butt End Fittings



Meter Size	PVC/CPVC in. (mm)				PVDF (Butt) in. (mm)			
	A	B	C	D	A	B	C	D
1/4 in. (6.3 mm)	3.81 (97)	1.75 (45)	5.25 (133)	2.5 (64)	5.9 (150)	0.63 (16)	4.87 (124)	1.31 (33)
1/2 in. (12.7 mm)	3.81 (97)	1.75 (45)	7.13 (181)	2.5 (64)	5.75 (146)	0.78 (20)	4.87 (124)	1.31 (33)
3/4 in. (19.1 mm)	3.81 (97)	1.75 (45)	7.63 (194)	2.5 (64)	5.75 (146)	0.94 (24)	4.87 (124)	1.44 (37)
1 in. (25.4 mm)	3.92 (100)	1.75 (45)	8.03 (204)	2.5 (64)	5.88 (149)	1.19 (30)	5.09 (129)	2 (51)
1-1/2 in. (38.1 mm)	3.9 (99)	2 (51)	8.37 (213)	2.5 (64)	6.21 (158)	1.50 (38)	6.24 (158)	2.50 (64)
2 in. (50.8 mm)	4.31 (109)	2 (51)	8.37 (213)	2.5 (64)	6.6 (168)	1.88 (48)	6.77 (172)	3 (76)

Wafer End Fittings



Meter Size	PVDF			
	A	B	C	D
1/2 in. (12.7 mm)	5.85 in. (149 mm)	0.78 in. (20 mm)	2.03 in. (52 mm)	1.75 in. (44 mm)
3/4 in. (19.1 mm)	5.90 in. (150 mm)	0.94 in. (24 mm)	2.03 in. (52 mm)	2.13 in. (54 mm)
1 in. (25.4 mm)	5.69 in. (145 mm)	1.19 in. (30 mm)	2.25 in. (57 mm)	2.47 in. (63 mm)
1-1/2 in. (38.1 mm)	6.00 in. (152 mm)	1.50 in. (38 mm)	2.63 in. (67 mm)	3.25 in. (83 mm)
2 in. (50.8 mm)	6.37 in. (162 mm)	1.88 in. (48 mm)	3.22 in. (82 mm)	4.00 in. (102 mm)
3 in. (76.2 mm)	6.88 in. (175 mm)	2.50 in. (64 mm)	4.25 in. (108 mm)	5.24 in. (133 mm)

PART NUMBER CONSTRUCTION

NPT End Fittings

RVL Piezoelectric Vortex Flow Meter
for Liquids (NPT Fittings)

Model		RVL	
Piezoelectric Vortex Flow Meter for Liquids (In-Line)			
Line Size			
1/4 Inch 5 gpm (19 lpm) Maximum Flow Rate		025	
1/2 Inch 15 gpm (56.8 lpm) Maximum Flow Rate		050	
3/4 Inch 25 gpm (94.6 lpm) Maximum Flow Rate		075	
1 Inch 50 gpm (189 lpm) Maximum Flow Rate		100	
1-1/2 Inch 100 gpm (379 lpm) Maximum Flow Rate		150	
2 Inch 200 gpm (757 lpm) Maximum Flow Rate		200	
Body Style			
NPT (Male) Thread		N	
Body Material			
PVC		1	
CPVC		2	
PVDF		4	
Output			
4 ... 20 mA			X
Rate Frequency Pulse Not Available with Display			P
Options ¹			
None			N
High Temperature Rated: 203° F (95° C) ²			H
Stainless Steel Tags			S
3-Pin (male) Output Connector ³			3
Display Mounting			
None			N
Top Mount			1
Right Mount			3

- Multiple Options may be listed in series on the part number - add as necessary
- High Temperature option ONLY available with Body Material options "2" and "4"
- When selecting Option 3, 3-Pin (male) Output Connector, a display cannot be mounted on the meter and Display Mounting must be marked as "N" for none.

Butt End Fittings


RVL Piezoelectric Vortex Flow Meter
for Liquids (Butt End Fittings)

Model		RVL	
Piezoelectric Vortex Flow Meter for Liquids (In-Line)			
Line Size			
1/2 Inch 15 gpm (56.8 lpm) Maximum Flow Rate		050	
3/4 Inch 25 gpm (94.6 lpm) Maximum Flow Rate		075	
1 Inch 50 gpm (189 lpm) Maximum Flow Rate		100	
1-1/2 Inch 100 gpm (379 lpm) Maximum Flow Rate		150	
2 Inch 200 gpm (757 lpm) Maximum Flow Rate		200	
Body Style			
Butt End Connection		B	
Body Material			
PVDF		4	
Output			
4 ... 20 mA			X
Rate Frequency Pulse Not Available with Display			P
Options ¹			
None			N
High Temperature Rated: 203° F (95° C) ²			H
Stainless Steel Tags			S
3-Pin (male) Output Connector ³			3
Display Mounting			
None			N
Top Mount			1
Right Mount			3

- Multiple Options may be listed in series on the part number - add as necessary
- High Temperature option ONLY available with Body Material option "4"
- When selecting Option 3, 3-Pin (male) Output Connector, a display cannot be mounted on the meter and Display Mounting must be marked as "N" for none.

Wafer End Fittings

RVL Piezoelectric Vortex Flow Meter
for Liquids (Wafer End Fittings)





Model							
Piezoelectric Vortex Flow Meter for Liquids (Wafer)		RVL					
Line Size							
1 Inch 50 gpm (189 lpm) Maximum Flow Rate		100					
1-1/2 Inch 100 gpm (379 lpm) Maximum Flow Rate		150					
2 Inch 200 gpm (757 lpm) Maximum Flow Rate		200					
3 Inch 300 gpm (1136 lpm) Maximum Flow Rate		300					
Body Style							
Wafer							W
Body Material							
PVC							1
CPVC							2
Polypropylene							3
PVDF							4
Output							
4 ... 20 mA							X
Rate Frequency Pulse Not Available with Display							P
Options ¹							
None							N
High Temperature Rated: 203° F (95° C) ²							H
Stainless Steel Tags							S
3-Pin (male) Output Connector ³							3
Display Mounting							
None							N
Top Mount							1
Right Mount							3



- 1.) Multiple Options may be listed in series on the part number - add as necessary
- 2.) High Temperature option ONLY available with Body Material options "2" and "4"
- 3.) When selecting Option 3, 3-Pin (male) Output Connector, a display cannot be mounted on the meter and Display Mounting must be marked as "N" for none..

PRESSURE DROP VS FLOW RATE

NPT/Butt End Fittings



Wafer End Fittings



Control. Manage. Optimize.

Trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2019 Badger Meter, Inc. All rights reserved.

www.badgermeter.com

The Americas | Badger Meter | 4545 West Brown Deer Rd | PO Box 245036 | Milwaukee, WI 53224-9536 | 800-876-3837 | 414-355-0400
México | Badger Meter de las Americas, S.A. de C.V. | Pedro Luis Ogazón N°32 | Esq. Angelina N°24 | Colonia Guadalupe Inn | CP 01050 | México, DF | México | +52-55-5662-0882
Europe, Eastern Europe Branch Office (for Poland, Latvia, Lithuania, Estonia, Ukraine, Belarus) | Badger Meter Europe | ul. Korfantego 6 | 44-193 Knurów | Poland | +48-32-236-8787
Europe, Middle East and Africa | Badger Meter Europa GmbH | Nurtinger Str 76 | 72639 Neuffen | Germany | +49-7025-9208-0
Europe, Middle East Branch Office | Badger Meter Europe | PO Box 341442 | Dubai Silicon Oasis, Head Quarter Building, Wing C, Office #C209 | Dubai / UAE | +971-4-371 2503
Slovakia | Badger Meter Slovakia s.r.o. | Racianska 109/B | 831 02 Bratislava, Slovakia | +421-2-44 63 83 01
Asia Pacific | Badger Meter | 80 Marine Parade Rd | 19-07 Parkway Parade | Singapore 449269 | +65-63464836
Switzerland | Badger Meter Swiss AG | Mittelholzerstrasse 8 | 3006 Bern | Switzerland | +41-31-932 01 11