



RXi2-EP Industrial PC

The Next Generation of Ruggedized Computing



GE's Automation & Controls has developed the next generation of its powerful, expandable, and reliable industrial computers (IPC). RXi2 IPCs offer new processor choices, increased and faster storage, improved graphics, and enhanced security features.

The RXi2-EP IPC delivers compact, rugged, mid-range performance computing capabilities to run HMI, historian, and analytics applications right at the machine to enable improved real-time control of operations and better integration into plant-wide systems.

Combining outstanding graphics capabilities with the added expandability of 0, 1, 2 or 4 PCI Express slots and CFast storage, the RXi2-EP is ideal for a range of demanding industrial applications.

High-Performance Computing

GE selected the latest Intel processors based on their unmatched performance. The RXi2-EP IPC has up to 16GB of ECC RAM, 5 Gigabit Ethernet interfaces, and industrial grade high-speed HDD storage (or optional SSD disk storage) to complete the high-performance design.

These features make the RXi2-EP IPC the perfect platform for running GE's Proficy* software applications or other industrial applications right at the machine, even in the harshest environments.

The RXi2-EP IPC provides additional application flexibility with both mini PCI Express and low-profile PCI Express slots. This expandability combined with advanced CPUs delivers high-performance, graphically powerful computing.

To help keep data and operations secure, the RXi2-EP utilizes Trusted Platform Module (TPM) and Secure Boot technology.

Greater Uptime

All aspects of the RXi2-EP IPC have been engineered for reliability in harsh environments, from the use of all industrial grade components to its fanless design.

The core of the RXi2-EP IPC architecture is GE's rugged COM Express modular CPU platform. GE incorporates patented thermal monitoring technology with sophisticated passive cooling techniques to provide the highest-performance, fanless industrial computing platform that can operate in extended temperature ranges.

Enhanced Productivity & Lower TCO

The RXi2-EP IPC combines high performance with reliability, enhancing productivity and reducing cost of ownership.

The RXi2-EP IPC delivers low TCO through features such as compact size, reduced maintenance, low power consumption, and ease of future performance upgrades enabled by our innovative rugged COM Express CPU architecture.

FEATURE	BENEFIT
2 nd Gen AMD R-Series APU	<ul style="list-style-type: none"> Delivers high-performance computing for applications that load, manipulate and store large amounts of data, or handle multiple communication ports in real-time
Fanless operation	<ul style="list-style-type: none"> A robust, reliable solution with no moving parts and minimized dust contamination
5 Gigabit Ethernet ports (four with Time SYNC IEEE1588 and 802.1AS)	<ul style="list-style-type: none"> Network implementation flexibility Multiple high-speed Ethernet links for communication-centric applications with support for deterministic transfer of data/commands
0, 1, 2 or 4 PCIe Expansion slots	<ul style="list-style-type: none"> Add new functionality on demand to support specific application needs

Specifications

Processor

- AMD RX-225FB Processor 15~17W CTDP 2c 2.2GHz (3.0GHz) 1MB Cache
- AMD RX-427BB Processor 30~35W CTDP 4c 2.7GHz (3.6GHz) 4MB Cache

Memory

- Up to 16 GB DDR3L-1866
- Soldered, with ECC

Storage Interfaces

- Primary storage device – M.2 PCI Express Gen3 x4 or M.2 SATA Gen3
- Secondary storage option – Twin 2.5" SATA drive bays, hot swap and RAID enabled
- CFast slot, user accessible, supports boot, hot plug

Ethernet

- Four 1-gigabit Ethernet channels – RJ-45 standard, SFP optional
- One 1-gigabit Ethernet channel w/ remote management capability – RJ45

Wireless Communication

- LTE modem option using Mini-PCIE with UIM card holder
- Wifi/Bluetooth radio option using M.2 expansion slot

Video/Graphics Interface

- Twin DisplayPort++ 1.2 for a total of 4 independent displays

USB Interface

- Four USB 3.0 external
- Two USB 2.0 internal

Serial Communications

- 2 to 4 channels
- Two RS232, two RS422/485

Expansion

- Mini-PCIE card site for NvSRAM card, LTE modem, or other
- M.2 communications slot for WiFi and Bluetooth
- PCI Express expansion slots:
 - Zero
 - One Gen3 x4
 - Two Gen2 x4
 - Four One Gen2 x4, 3 Gen2 x1

Non-Volatile Memory

- 512 KB, 1MB or 2MB NvSRAM
- Storage for process relevant data
- NvSRAM option uses mini-PCIE slot

LED

- Power, TPM, Temperature, SATA
- Ethernet Link/Activity
- One User Defined LED

Others

- Timers: Legacy PC-AT, HPET
- Twin Watchdog Timers (OS, application)
- Thermal monitoring
- RTC with Lithium coin cell battery

Power

- Input: 24V DC (±25%) with protection

Environmental

All values under typical conditions without added expansion slot cards.

Extended temperature variants are available upon request.

The maximum extended temperature ranges mentioned in the table below are achievable with a specific choice of CPU and storage, and without extension cards installed in the system.

For detailed information please read the manual.

Range	Operating	Storage
Standard	Refer to Ordering Information table ¹	-40°C to +85°C
Extended	Up to -20°C to 60°C are achievable on request. With special SSDs and components even -30°C and -40°C are achievable on request.	-40°C to +85°C

¹ Temperature rating requires vertical orientation of the heat sink fins.

	Operating	Storage
Humidity	5-95% @ +40°C	5-95% @ +40°C
Altitude	6,600 ft. (2.0km)	40000 ft. (12 km)

BIOS

- UEFI AMI Aptio® 5

Dimensions (H x W x D)

- 0 slot: 252 x 203 x 108.5 mm (9.92 x 8 x 4.24 in)
Weight: 4,2kg
- 2 slot: 252 x 203 x 155.5 mm (9.92 x 8 x 6.13 in)
Weight: 4,4kg

Mechanical

- Rugged aluminum and stainless steel housing for optimal thermal management and durability
- IP20 – Protection against particles
- Flat and Slim (Book) mounting orientation options

Software Support

- Microsoft® Windows® 7 Professional 64-Bit
- Microsoft® Windows® 10 Professional 64-Bit
- Linux kernel 4.4
- VXWorks 7.0

Safety

- Designed to meet standard UL1950, CE class A, FCC-A
- Designed to meet marine class A



Slim version available

Ordering Information

PART NUMBER	DESCRIPTION	OPERATING TEMPERATURE
R2E0N1A0A1TOA	Quad Core 2.7GHz, 0 Slot, 128GB SSD, 16GB DDR3L, 2xRS232, 5xRJ45, No OS	0°C to +60°C
R2E0N1A1A1TOA	Quad Core 2.7GHz, 0 Slot, 128GB SSD, 16GB DDR3L, 2xRS232, 5xRJ45, Windows 10	0°C to +60°C
R2E0N1C0A1TOA	Dual Core 2.2GHz, 0 Slot, 128GB SSD, 8GB DDR3L, 2xRS232, 5xRJ45, No OS	0°C to +60°C
R2E0N1C1A1TOA	Dual Core 2.2GHz, 0 Slot, 128GB SSD, 8GB DDR3L, 2xRS232, 5xRJ45, Windows 10	0°C to +60°C
R2E2N1A0A2TOA	Quad Core 2.7GHz, 2 Slot, 128GB SSD, 16GB DDR3L, 2xRS232, 2xRS422/485, 5xRJ45, No OS	0°C to +60°C
R2E2N1A1A2TOA	Quad Core 2.7GHz, 2 Slot, 128GB SSD, 16GB DDR3L, 2xRS232, 2xRS422/485, 5xRJ45, Windows 10	0°C to +60°C
R2E2N1C0A2TOA	Dual Core 2.2GHz, 2 Slot, 128GB SSD, 8GB DDR3L, 2xRS232, 2xRS422/485, 5xRJ45, No OS	0°C to +60°C
R2E2N1C1A2TOA	Dual Core 2.2GHz, 2 Slot, 128GB SSD, 8GB DDR3L, 2xRS232, 2xRS422/485, 5xRJ45, Windows 10	0°C to +60°C

Accessories

TBD	10 pcs Flat Mounting Kit
TBD	1 pcs Flat Mounting Kit
TBD	1 pcs Slim 70 Mount Kit RXE (for 2-4 slot RXi-XP)

GE Energy Connections
Automation & Controls
2500 Austin Dr
Charlottesville, VA 22911
1-800-433-2682 or 1-434-978-5100
www.geautomation.com

© 2017 General Electric. The GE brand and logo are trademarks of General Electric. All other trademarks are the property of their respective owners. Specifications are subject to change without notice.

07.17 GFA2130