



Co-Processor and Serial Communications Modules

RX3i features a wide range of Specialty Modules to meet all of your application needs. From temperature controls, high-speed counters, I/O processors, coprocessors, to PID auto-tuning modules, these Specialty Modules are designed to meet the demand for versatile industrial solutions.

	IC695CMM002	IC695CMM004	IC695PRS015	HE693ASC900
Product Name	Two Port Serial Module	Four Port Serial Module	Pressure Transducer Module supporting Honeywell LG1237 Smart Sensors	Horner ASCII Basic Module
Lifecycle Status	Active	Active	Active	Active
Module Type	Serial Communications 2 Isolated Serial Ports	Serial Communications 4 Isolated Serial Ports	Serial Communications	Serial Communications 4 Isolated Serial Ports ASCII Basic Co-Processor
Backplane Support	Universal Backplane Only. Uses PCI Bus	Universal Backplane Only. Uses PCI Bus	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Protocols Supported	Serial Read/Write Modbus Master/Slave DNP 3.0 Master/ Slave CCM Slave and Custom Protocols	Serial Read/Write Modbus Master/Slave DNP 3.0 Master/ Slave CCM Slave and Custom Protocols	Pressure Transducer Honeywell LG1237 Smart Pressure Transducer sensors (Up to 15 sensors)	N/A
Programming Languages	None required. Communications set up in Machine Edition	None required. Communication set up in Machine Edition		BASIC
Program Storage	FLASH	FLASH	FLASH	EEPROM
Communication Ports	(2) Isolated RS-232 or RS-485/422	(4) Isolated RS-232 or RS-485/422	(1) RS-485	RS-232, RS-232/485
Network Data Rate	Selectable Baud Rates: 1200, 2400, 4800, 9600, 19.2K, 38.4K, 57.6K, 115.2K	Selectable Baud Rates: 1200, 2400, 4800, 9600, 19.2K, 38.4K, 57.6K, 115.2K	375K baud	N/A
Internal Power Used	0.7 Amps maximum @ 3.3 VDC 0.115 Amps maximum @ 5 VDC	0.7 Amps maximum @ 3.3 VDC 0.150 Amps maximum @ 5 VDC	0.7 Amps maximum @ 3.3 VDC 0.115 Amps maximum @ 5.0 VDC	375 mA @ 5 VDC