

Duct Leakage Testers



Model PAN200

Features and Benefits

- Positive and Negative Duct Leakage Testing in one system
- Find and fix duct leaks to save energy
- High accuracy gives confidence in measurements
- High-flow fan for testing large duct sections
- Pressurizes duct quickly, allowing testing to begin in minutes
- Fits in the back of vans and trucks
- Includes TSI Model 9565-P and Model 5825 instruments:
 - Automatically calculate leakage rate in real time
 - Simultaneously displays flow leakage rate and static pressure
 - Monitors barometric pressure and temperature to automatically correct to Standard Temperature and Pressure (STP)
 - Simplify report generation and documentation by downloading stored data
 - Works with Model 8934 Portable Printer for field documentation

Positive and Negative Duct Accreditation (PANDA) System

Model PAN200 Series

The Positive and Negative Duct Accreditation (PANDA) system provides contractors, commissioning engineers, and research and development technicians with the best in class choice of test equipment to quantify air leakage in ductwork and other areas as well as the ability to measure the performance of ducted systems. The PANDA system provides a fast, accurate, automated solution and helps to ensure compliance with SMACNA, EN12237, EN1507, and EUROVENT 2/2 standards, enhancing energy savings in buildings.

Pass/Fail Reporting for Standards

- SMACNA HVAC Air Duct Leakage Test Manual
- EN12237 Ventilation for Buildings—Ductwork—Strength & Leakage of Circular Sheet Metal Ducts
- EN1507 Ventilation for Buildings—Sheet Metal Ducts with Rectangular Section—Requirements for Strength and Leakage
- EUROVENT 2/2 Air Leakage Rate in Sheet Metal Air Distribution Systems



TRUST. SCIENCE. INNOVATION.

Duct Leakage Testers

Specifications

Model PAN200 Series

Pressure Measurement (5825)

Range	±15 in. W.G. (±3,735 Pa)
Resolution	0.001 in. W.G. (0.1 Pa)
Accuracy	1% of reading ±0.005 in. W.G. (±1 Pa)
Actual Duct Static Range	±10 in. W.G. (±2,500 Pa) at Zero Flow

Volume Flow Measurement (9565-P)

High leakage range	Wilson Radial Flow Grid 21 to 424 cfm (10 to 200 l/s), 36 to 720 m ³ /hr
Low leakage range	Conical Inlet Nozzle Adapter 2 to 27.5 cfm (1 to 13 l/s), 3.6 to 46.9 m ³ /hr,
Resolution	0.01 cfm (0.01 l/s), 0.01 m ³ /hr
Accuracy	±2.5% of reading ±0.02 cfm (±0.01 l/s), ±0.04 m ³ /hr

Temperature Measurement (9565-P)

K Type thermocouple probe	To EN60584 (IEC 584)
Range	-40 to 1200°F (-40 to 650°C)
Resolution	0.1°F (0.1°C)
Accuracy	±0.1% of reading ±2°F (±0.056% of reading ±1.1°C)

Barometric Pressure Measurement (9565-P)

Range	20.36 to 36.648 in. Hg (690 to 1,241 hPa), 517.5 to 930.87 mm Hg
Accuracy	±2% of reading

Power requirements

Model PAN221	220 to 240 V, 1 Phase, 50/60 Hz, 10A
Model PAN221-110	110 to 120 V, 1 Phase, 50/60 Hz, 16A

Weight

157 lbs (71 kg)

Dimensions (L x W x H)

44.5 in. x 26 in. x 20 in. (1,130 mm x 660 mm x 510 mm)

PAN221, PAN221-110

Instruments included

VELOCI-CALC® Model 9565-P meter,
DP-CALC™ Model 5825 micromanometer.
See spec sheets for details on
individual instruments.



Model 9565-P



Model 5825

Specifications subject to change without notice.
TSI, TSI logo, VELOCI-CALC, and DP-CALC are trademarks of TSI Incorporated.

TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA	Tel: +1 800 874 2811	E-mail: info@tsi.com	Website: www.tsi.com
UK	Tel: +44 149 4 459200	E-mail: tsiuk@tsi.com	Website: www.tsiinc.co.uk
France	Tel: +33 491 11 87 64	E-mail: tsifrance@tsi.com	Website: www.tsiinc.fr
Germany	Tel: +49 241 523030	E-mail: tsigmbh@tsi.com	Website: www.tsiinc.de
India	Tel: +91 80 41132470	E-mail: tsi-india@tsi.com	
China	Tel: +86 10 8251 6588	E-mail: tsi-beijing@tsi.com	
Singapore	Tel: +65 6595 6388	E-mail: tsi-singapore@tsi.com	



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.