

Thermocouples

Mineral Insulated

Watlow's mineral insulated thermocouples are fast-responding, durable, and capable of handling high temperatures.

These thermocouples are manufactured with best-in-class XACTPAK®, Watlow's trademark for metal sheathed, mineral insulated (MI) thermocouple material. XACTPAK responds fast because the protective metal outer sheath allows the use of smaller diameter thermocouple conductors. The rock hard compacted MgO insulation further enhances the sensor's ability to "read" temperature by transferring heat quickly to the measuring junction.

The XACTPAK protecting sheath and compacted insulation outperforms bare wire thermocouples in most applications.

Performance Capabilities

- Easily handles temperatures up to 1200°C (2200°F)
- Meets or exceeds initial calibration tolerances per ASTM E 230

Features and Benefits

Special mineral insulation

- Protects thermocouple from moisture and thermal shock
- Permits operation in high temperature, high pressure environments

Diameters as small as 0.010 in. (0.25 mm)

- Ideal when physical space or extremely fast response are critical

Flexibility of the XACTPAK material

- Allows you to form and bend the thermocouple, without risk of cracking, to meet your design requirements



Outer sheath

- Protects the wires from oxidation and hostile environments

Wide range of sheath materials, diameters, and calibrations

- Meet specific requirements

In-house manufacturing of XACTPAK material

- Rigid quality control procedures
- Assures high standards are met
- Single source reliability

Custom capabilities

- Include options such as special lead lengths, lead wires and terminations


Applications

- Heat treating
- Furnaces/kilns
- Turbines
- Bearing temperature
- Power stations
- Steam generators
- Diesel engines
- Nuclear reactors
- Atomic research
- Jet engines and test cells
- Rocket engines
- Semiconductor manufacturing
- Refineries/oil processing
- Catalytic reformers
- Food processing

Thermocouples

Mineral Insulated

Cut and Stripped Style AB



The main feature of Watlow's Style AB thermocouple is it allows you to terminate the thermocouple yourself. Style AB is simply a section of XACTPAK material, junctioned and stripped. It is the most basic of all the mineral insulated thermocouple styles.

Because it is constructed with XACTPAK mineral insulation, the thermocouple is protected from moisture, thermal shock, high temperatures and high pressure.

Performance Capabilities

- Maximum temperature depends on sheath material, calibration, and other variables

Features and Benefits

Cold end stripped and sealed with epoxy

- Inhibits moisture penetration

Dual element style

- Allows you to run two instruments off the same element, reducing your costs

Custom Ordering Information—Items in **Bolded Green Type** are preferred with shorter lead times.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	A	B		0		0									
3. Sheath O.D. (inch)															
A = 0.010	E = 0.063	L = 0.375													
B = 0.020	G = 0.125	M = 0.500													
C = 0.032	H = 0.188														
D = 0.040	J = 0.250														
4. Enter "0"															
5. Fittings, Weld Pads															
If required, enter order code from pages 39-40. If none, enter "0".															
6. Enter "0"															
7. Sheath Material															
A = 304 SS	Q = Alloy 600 (Type K)														
F = 316 SS															
8-9. Sheath Length "L" (whole inches)															
01 to 99 Lengths over 99 inches consult factory.															
10. Sheath Length "L" (fractional inch)															
0 = 0	4 = 1/2														
1 = 1/8	5 = 3/8														
2 = 1/4	6 = 1/2														
3 = 3/8	7 = 5/8														
11. Junction															
	Grounded			Ungrounded			Exposed								
Single	G			U			E								
Dual	H			W (isolated)			D (isolated)								
12. Calibration															
	E	J	K	N	T										
Standard limits	E	J	K	N	T										
Special limits	2	3	4	—	8										
13. Strip Length "S" (whole inches)															
0, 1, 2 and 3 - 1 inch maximum on 0.040 and smaller															
14. Strip Length "S" (fractional inch)															
0 = 0	4 = 1/2														
1 = 1/8	5 = 3/8														
2 = 1/4	6 = 1/2														
3 = 3/8	7 = 5/8														
15. Special Requirements															
0 = None															
X = Special requirements, consult factory															