







Parameters:

pH units Temperature °C mV/ORP/Redox (oxidation reduction potential) mV



EcoSense® pH100M pH/ORP/mV/Temperature

Accurate, economical, handheld instrument

The YSI EcoSense® instruments provide accurate data in the most affordable format. The "M" stands for memory and the instruments feature a real-time clock, larger memory and simple data transfer to a PC with a built-in USB port.

The pH100M is easy-to-use, field-worthy and provides accurate and repeatable measurements.

The pH100M measures pH, mV/ORP and temperature with the following features:

- Rugged, waterproof, field-worthy case. IP-67 rated.
- Waterproof micro-USB port for transferring data to PC; no software required.
- Holds 250 data sets; no need to write down data.
- Real-time clock for date/time stamp of saved data.
- User-selectable re-calibration prompt provides reminder to calibrate.
- Automatic buffer recognition (US or NIST buffer sets).
- Automatic or manual temperature compensation.
- 1-year instrument warranty; 6-month electrode warranty.
- 1 and 4-meter field cables available; lab pH and ORP electrodes available.
- Displays electrode efficiency.
- Autolock mode holds stable readings on display.

The pH100M is designed for quick, accurate measurements in an economical platform. Easy-to-use, waterproof and backed by a 1-year warranty, the pH100M is ideal for a wide range of applications.

EcoSense pH100M Instrument Only Specifications

Temperature	Range	-10 to 120°C
	Resolution	0.1°C
	Accuracy	± 0.3 °C (System accuracy - instrument, sensor, cable)
рН	Range	-2 to 16 units
	Resolution	0.01 unit
	Accuracy	$\pm 0.01\%$ of full scale or ± 0.03 pH units (System accuracy - instrument, sensor, cable: ± 0.2 pH units)
mV	Range	-1999 to +1999 mV
	Resolution	1 mV

EcoSense pH100M Additional Specifications

Accuracy

Operating range	remperature	0 10 30 C(32 10 122 1)
	Relative Humidity	up to 95%
Waterproof rating	IP-67 waterproof	

Handheld Size 78 mm wide (widest point) x 184 mm long x 37 mm deep (3.1 in x 7.25 in x 1.45 in)

<u>+</u>0.1% <u>+</u>1 digit

 $\begin{array}{ll} \mbox{Weight with battery} & 280 \mbox{ grams (0.6 lb)} \\ \mbox{ATC Probe} & \mbox{Thermistor, } 10 \mbox{k}\Omega/25^{\circ}\mbox{C} \end{array}$

Battery One 9 volt (included); 150 hour battery life; Real Time Clock (RTC) powered by non-replaceable CR2032 coin battery (3V)

pH Temperature Compensation Auto/Manual -10.0°C to 120.0°C (14 to 248°F)

pH Buffer Recognition US (4.00, 7.00 & 10.0 at 25°C or 4.00, 7.02 & 10.06 at 20°C) or NIST (4.01, 6.86, 9.18 at 25°C or 4.00, 6.87 & 9.23 at 20°C)

pH Calibration Temperature 0°C to 60 °C (32 to 140°F)
pH Offset Recognition +90 mV at pH 7.00 or 6.86

pH Slope Recognition +30% at pH 4.00, 4.01, 9.18, or 10.01

Audio Feedback Yes, all keys
Autolock feature Yes

Auto shutoff
Automatically powers off after 30 minutes of inactivity
Memory (data sets)
250 (1 data set = pH, temperature, date/time)

Re-calibration Timer User-selectable; from 0 to 60 days

Real-Time Clock (RTC)

Yes, for date/time stamp of saved data and re-calibration timer

USB Port Yes, built-in waterproof micro-USB for downloading data to a PC. No software required.

EcoSense pH100M Ordering Information (order items separately or as a kit)

601031	pH100M, meter only - includes manual, USB cable and 9 volt battery
601032	Kit: pH100M meter, 1 meter cable/probe assembly, carrying case
601033	Kit: pH100M meter, 4 meter cable/probe assembly, carrying case
605377	1-meter waterproof field cable with combo pH electrode and temperature
605378	4-meter waterproof field cable with combo pH electrode and temperature
605374	1-meter pH laboratory grade cable and electrode
605080	1-meter pH piercing tipped, double-junction cable and electrode
605081	1-meter pH flat tipped, double junction cable and electrode
605376	1-meter ORP laboratory grade cable and electrode
605375	1-meter temperature cable and probe
606031	Hard-sided, plastic carrying case with form fitted foam insert; 31.75 x 22.86 x 9.4 cm (12.5 x 9 x 3.7 in)
605380	pH 4, 7, 10 electrode simulator (ensures instrument performance)
603824	pH Buffers; Assorted case of 2 pints each of 4, 7 and 10







YSI Incorporated

1725 Brannum Lane

Yellow Springs, OH 45387

U 1.800.897.4151

info@ysi.com

YSI.com









