
SUW611

Ultrasonic flow meter

SUF80IGBFRKG/US



Product characteristics				
Measuring range	25...3600 l/min	1.5...216 m³/h	400...57061 gph	6.6...951 gpm
Nominal diameter	DN80 (3“)			
Process connection	3" ASME B16.5 Class 150 flange (ASME BPE)			

Application		
Special feature	Gold-plated contacts	
Application	use in industrial applications	
Media	ultra-pure water; water; hydrous media; glycol solutions	
Note on media	hydrous media: for media with >10 % additives, the repeatability is the only available value	
Medium temperature	[°C]	-20...100

SUW611

Ultrasonic flow meter

SUF80IGBFRKG/US

Min. burst pressure	40 bar	928 psi	4 MPa	
Pressure rating	16 bar	232 psi	1.6 MPa	
Vacuum resistance [mbar]	-1000			
Electrical data				
Operating voltage [V]	18...32 DC; (to SELV/PELV)			
Current consumption [mA]	< 75			
Protection class	III			
Reverse polarity protection	yes			
Power-on delay time [s]	5			
Measuring principle	ultrasonic			
Inputs / outputs				
Total number of inputs and outputs	2			
Inputs				
Inputs	OUT2	counter reset		
Outputs				
Total number of outputs	2			
Output signal	OUT1	switching signal; pulse signal; diagnostic signal; totaliser switching signal; frequency signal; IO-Link		
	OUT2	switching signal; pulse signal; diagnostic signal; totaliser switching signal; analogue signal		
Electrical design	PNP/NPN			
Pulse output	flow rate meter			
Short-circuit protection	yes			
Type of short-circuit protection	pulsed			
Overload protection	yes			
Analogue				
Number of analogue outputs	1			
Analogue current output [mA]	4...20			
Max. load [Ω]	500			
Digital				
Number of digital outputs	2			
Output function	normally open / normally closed; (parameterisable)			
Max. voltage drop switching output DC [V]	2			
Permanent current rating of switching output DC [mA]	100			
Switching frequency DC [Hz]	0...10000			
Measuring/setting range				
Measuring range	25...3600 l/min	1.5...216 m³/h	400...57061 gph	6.6...951 gpm
Display range	-4320...4320 l/min	-259.2...259.2 m³/h	-68473...68473 gph	-1141.22...1141.22 gpm
Resolution	0.1 l/min	0.001 m³/h	1 gph	0.01 gpm
Note on factory setting	gpm, °F			

SUW611

Ultrasonic flow meter

SUF80IGBFRKG/US

Set point SP	44.8...3600 l/min	2.7...216 m³/h	710...57061 gph	11.8...951 gpm
Reset point rP	26.1...3581.3 l/min	1.6...214.9 m³/h	413...56764 gph	6.9...946.1 gpm
Analogue start point ASP	-3600...2880 l/min	-216...172.8 m³/h	-57060...45650 gph	-951...760.8 gpm
Analogue end point AEP	-2880...3600 l/min	-172.8...216 m³/h	-45650...57060 gph	-760.8...951 gpm
Low flow cut-off LFC	25...180 l/min	1.5...10.8 m³/h	400...2850 gph	6.6...47.6 gpm
Frequency end point, FEP	722.2...3600 l/min	43.3...216 m³/h	11450...57060 gph	190.8...951 gpm
Frequency at the end point FRP [Hz]	1...10000			
Volumetric flow quantity monitoring				
Pulse length [s]	0.002...2			
Pulse value	0.1...99990000 l; 0.026…26414563.515 gal			
Temperature monitoring				
Measuring range	-20...100 °C		-4...212 °F	
Display range	-44...124 °C		-47.2...255.2 °F	
Resolution	0.1 °C		0.1 °F	
Set point SP	-19.6...100 °C		-3.2...212 °F	
Reset point rP	-20...99.6 °C		-4...211.2 °F	
Analogue start point	-20...76 °C		-4...168.8 °F	
Analogue end point	4...100 °C		39.2...212 °F	
Frequency start point, FSP	-20...76 °C		4...168.8 °F	
Frequency end point, FEP	4...100 °C		39.2...212 °F	
Frequency at the end point FRP [Hz]	1...10000			
Accuracy / deviations				
Flow monitoring				
Accuracy (in the measuring range)	water		± (2,0 % MW + 0,5 % MEW)	
Repeatability	± 0,2 % MEW			
Temperature monitoring				
Accuracy [K]	± 2,5 (Q > 5 % MEW)			
Temperature coefficient [% of the span / 10 K]	0,2			
Response times				
Flow monitoring				
Response time [s]	< 0.5; (dAP = 0, T09)			
Damping process value dAP [s]	0...5			
Temperature monitoring				
Dynamic response T05 / T09 [s]	5,7 / 86			
Software / programming				
Diagnostic functions	direction of flow detection; signal quality			
Interfaces				
Communication interface	IO-Link			
Transmission type	COM2 (38,4 kBaud)			
IO-Link revision	1.1			
SDCI standard	IEC 61131-9			

SUW611

Ultrasonic flow meter

SUF80IGBFRKG/US

Profiles		BLOB	Binary Large Object transfer
		Common - I&D	Identification and Diagnosis
Required master port type		A	
Process data analogue		3	
Process data binary		2	
Min. process cycle time	[ms]	9.6	
IO-Link process data (cyclical)		**function**	**bit length**
		totaliser	32
		Flow monitoring	32
		Temperature monitoring	32
		status	4
		Output 1	1
		Output 2	1
Supported DeviceIDs		**Type of operation**	**DeviceID**
		default	2014
Operating conditions			
Ambient temperature	[°C]	-20...60	
Storage temperature	[°C]	-25...80	
Protection		IP 65; IP 67	
Tests / approvals			
EMC		DIN 61326-1:2021	
Shock resistance		DIN IEC 68-2-27	20 g (11ms)
Vibration resistance		DIN IEC 68-2-6	20 g (10...2000Hz)
UL approval		UL approval no.	I033
		File number UL	E174189
Pressure Equipment Directive		can be used for group 2 fluids; group 1 fluids on request	
Mechanical data			
Weight	[g]	57.9	
Housing		rectangular	
Inlet pipe length		15 x DN	
Outlet pipe length		3 x DN	
Dimensions	[mm]	250 x 190 x 195.4	
Materials		housing: stainless steel (316L/1.4404); Display: PFA; Sealing Display: FKM; connector: PBT	
Materials (wetted parts)		Pipe section: stainless steel (316L/1.4435); Process connection: stainless steel (316L/1.4404)	
Nominal diameter		DN80 (3“)	
Process connection		3" ASME B16.5 Class 150 flange (ASME BPE)	
Surface characteristics Ra/Rz of the wetted parts		Ra < 0.76 µm	
Displays / operating elements			
Display			colour display 1,44", 128 x 128 pixels
		Switching function	2 x LED, yellow
		diagnosis	1 x LED, three-colour
Display unit		l/min; l/h; m³/h; m/s; gpm; gph; ft/s	
Accessories			
Items supplied		package insert	

SUW611

Ultrasonic flow meter

SUF80IGBFRKG/US

Remarks


Remarks	MW = measured value
	MEW = Final value of the measuring range
	pulse and totaliser signal are only available for one of the two outputs
	the specified Ra surface characteristics of the wetted surfaces do not apply to the weld seam.
Pack quantity	1 pcs.

Electrical connection - plug

Connector: 1 x M12; coding: A; Contacts: 4, gold-plated




Connection



1 (L+)	L+	
2 (OUT2)	MP2	DO2, AO, DI
3 (L-)	L-	
4 (OUT1)	MP1	DO1, FO, IO-Link

AO: analogue output; DI: digital input; DO: digital output; FO: frequency output; MP: multi-function connection

Diagrams and graphs



dP [psi] Pressure loss

Q [gpm] volumetric flow quantity