Midas[®] sensor cartridge specifications

Carbon Monoxide (CO) MIDAS-S-COX, MIDAS-E-COX

Gas Measured	Carbon Monoxide (CO)	
Cartridge Part Number	MIDAS-S-COX 1 year standard warranty MIDAS-E-COX 2 year extended warranty	
Sensor Technology	3 electrode electrochemical cell	
Measuring Range (ppm)	CO 0 – 100ppm	
Minimum Alarm 1 Set Point	12.5ppm	
Lower Detectable Limit (LDL)	9.0ppm	
Repeatability	$< \pm 2\%$ of measured value	
Linearity	$<\pm$ 2% of measured value	
Response Time t _{62.5}	≤ 60 seconds	
Sensor Cartridge Life Expectancy	≥ 24 months under typical application conditions	
Operating Temperature	0°C to + 40°C (32°F to 104°F)	
Effect of Temperature Zero Sensitivity	$< \pm 0.035$ ppm / °C $< \pm 0.8\%$ of measured value / °C	
Operating Humidity (continuous) Effect of Humidity Zero Sensitivity	$15-90\%$ rH $$<\pm0.02ppm$ of measured value / % rH No effect	
Operating Pressure	70 – 110kPa	
Effect of Position	No effect in typical application	
Long Term Drift Zero Sensitivity	< 2ppm / year < ± 5% of measured value / year	
Calibration Gas	Carbon Monoxide (CO)	
Challenge Gas (Bump Test)	Carbon Monoxide (CO)	
Warm Up Time	< 10 minutes	
Storage Temperature	+5°C to +25°C (+41°F to +77°F)	



Honeywell

Cross Sensitivities

Each Midas[®] sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration Applied (ppm)	Reading (ppm CO)
Acetone	(CH ₃) ₂ CO	1000	0
Acetylene	C_2H_2	40	80
Ammonia	NH ₃	100	0
Carbon Monoxide	CO	100	100
Chlorine	Cl ₂	2	0
Ethanol	C_2H_5OH	2000	3
Ethylene	C_2H_4	100	110
Hydrogen	H ₂	100	35
Hydrogen Sulphide	H_2S	25	0
Iso Propanol	C ₃ H ₇ OH	200	0
Nitric Oxide	NO	50	8
Nitrogen Dioxide	NO ₂	800	20
Sulphur Dioxide	SO ₂	50	0.5

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed

Find out more

www.honeywellanalytics.com Toll-free: 800.538.0363

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.