Honeyweg

Midas[®] sensor cartridge specifications

Hydrogen ppm (H₂) MIDAS-S-H2X, MIDAS-E-H2X

Gas Measured	Hydrogen (H ₂)		
Cartridge Part Number	MIDAS-S-H2X 1 year standard warranty MIDAS-E-H2X 2 year extended warranty		
Sensor Technology	3 electrode electrochemical cell		
Measuring Range (ppm)	H ₂ 0 – 1000ppm		
Minimum Alarm 1 Set Point	120ppm		
Lower Detectable Limit (LDL)	90ppm		
Repeatability	$< \pm$ 5% of measured value		
Linearity	$<\pm$ 5% of measured value		
Response Time t _{62.5}	< 50 seconds		
Sensor Cartridge Life Expectancy	≥ 24 months under typical application conditions		
Operating Temperature Effect of Temperature Zero Sensitivity	0°C to +40°C (32°F to 104°F) < ± 0.17ppm / °C (0°C to 20°C) < ± 0.07ppm / °C (20°C to 40°C) < ± 3% of measured value / °C		
Operating Humidity (continuous) Effect of Humidity Zero Sensitivity	10 – 90% rH No effect No effect		
Operating Pressure	90 – 110 kPa		
Effect of Position	No effect in typical application		
Long Term Drift Zero Sensitivity	No drift $< \pm 10\%$ of measured value / 6 month		
Calibration Gas	Hydrogen (H ₂)		
Challenge Gas (Bump Test)	Hydrogen (H ₂)		
Warm Up Time	< 10 minutes		
Storage Temperature	+5°C to +25°C (+41°F to + 77°F)		



Honeywell

Cross Sensitivities

Each Midas[®] sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration Applied (ppm)	Reading (ppm H ₂)
Ammonia	NH ₃	100	0
Arsine	AsH ₃	0.2	0
Carbon Dioxide	CO ⁵	1000	0
Carbon Monoxide	CO	100	150
Chlorine	Cl ₂	1	0
Chlorine Dioxide	CIO ₂	1	0
Hydrogen Cyanide	HCN	20	0
Hydrogen Sulphide	H_2S	20	4
Iso Propanol	C ₃ H ₇ OH	1100	Yes
Methane	CH_4	1%	0
Nitrogen Dioxide	NO ₂	10	-40
Ozone	03	0.25	0
Sulphur Dioxide	SO ₂	5	0

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed

Find out more

www.honeywellanalytics.com Toll-free: 800.538.0363

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.