# **Midas**<sup>®</sup> sensor cartridge specifications

## Ozone (O<sub>3</sub>) MIDAS-E-O3H

Gas Measured	Ozone (0 <sub>3</sub> )	
Cartridge Part Number	MIDAS-E-03H 2 year extended warranty	
Sensor Technology	3 electrode electrochemical cell	
Measuring Range (ppm)	0 <sub>3</sub> 0 – 0.7ppm	
Minimum Alarm 1 Set Point	0.085ppm	
Lower Detectable Limit (LDL)	0.065ppm	
Repeatability	$< \pm 5\%$ of measured value	
Linearity	$< \pm 5\%$ of measured value	
Response Time t <sub>62.5</sub>	< 60 seconds	
Sensor Cartridge Life Expectancy	≥ 24 months under typical application conditions	
Operating Temperature Effect of Temperature Zero Sensitivity	0°C to +40°C (32°F to 104°F) < ± 0.0008 ppm / °C < ± 5% / °C	
Operating Humidity (continuous) Effect of Humidity Zero Sensitivity	20 - 75% rH Abrupt changes will cause a short term drift $< \pm 1\%$ of measured value / % rH	
Operating Pressure	90 - 110kPa	
Effect of Position	No effect in typical application	
Long Term Drift Zero Sensitivity	No drift < 5% of measured value / 1 Year	
Calibration Gas	Ozone (0 <sub>3</sub> )	
Challenge Gas (Bump Test)	Nitrogen Dioxide (NO <sub>2</sub> )	
Warm Up Time	< 10 minutes	
Storage Temperature	+5°C to +25°C (+41°F to +77°F)	



Honeywell

#### **Cross Sensitivities**

Each Midas<sup>®</sup> sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration applied (ppm)	Reading (ppm $O_3$ )
Carbon Dioxide	CO <sup>5</sup>	20000	0
Chlorine	$Cl_2$	1	1.2
Chlorine Dioxide	CIO <sub>2</sub>	1	1.75
Hydrogen Chloride	HCI	9	1.63
Hydrogen Sulphide	$H_2S$	25	-15.5 (Transient)
Nitrogen Dioxide	NO <sub>2</sub>	6	2.5
Sulphur Dioxide	SO <sub>2</sub>	10	-3 (Transient)

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed

### Find out more

www.honeywellanalytics.com Toll-free: 800.538.0363

#### Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.