



Level



Pressure



Flow



Temperature



Liquid Analysis



Registration



Systems Components



Services



Solutions

## Technical Information

# Omnigrad S TC66

Thermocouple thermometer EEx-d certified, replaceable insert, thermowell from bar stock, process connection: threaded or flanged PCP (4...20 mA), HART® or PROFIBUS-PA® electronics



### Range of uses

The Omnidgrad S TC66 is an industrial thermometer (thermocouple TC: K or J) with a replaceable inset, a neck and a thermowell from bar stock.

It is developed for the use in the chemical, petrochemical and energy industries, but suitable also for other generic heavy duty applications.

In compliance to EN 50014/18/20 (ATEX certification) it is therefore particularly suitable also for hazardous areas.

When required, it's also available with a transmitter (PCP, HART® or PROFIBUS-PA®) into the housing.

The process connection of the thermowell is threaded or flanged in compliance to the standard of process requirements.

### Application areas

- Chemicals industry
- Energy industry
- Gas Processing industry
- Petrochemical industry
- General industrial services

### Features and benefits

- Several types of process connection
- Several type of materials available for the thermowells
- Customized immersion length
- Aluminium housing, with protection grade from IP66 to IP68
- Thermocouple with hot junction grounded or ungrounded in mineral oxide cable (MgO cable) diameter: 3 or 6 mm
- PCP, HART® and PROFIBUS-PA®, (4...20 mA 2-wire transmitters)
- The accuracy of the thermocouple TC (K (NiCr-Ni) and J (Fe-CuNi)) are: Cl. 1 - 2 (EN 60584) or Cl. Special - Standard (ANSI MC96.1)
- The thermocouple TC (K or J) are available in single or double element
- ATEX II 2 GD EEx-d IIC certification
- ATEX II 1/2 GD EEx d IIC certification



## Function and system design


### Measuring principle

The thermocouple (TC) thermometer's sensing element consists of two metal wires that are homogeneous but different one from the other and insulated along their entire length. The two wires are welded together at one end, known as the "measurement or hot junction". The other end, where the wires are free, is known as the "cold or reference junction" and is connected to a electromotive force measurement circuit where the force is generated by the different thermoelectric power of each of the thermocouple's wires if there is a temperature difference between the hot joint (T1) and the cold joint (Seebeck effect). The cold junction has to be "compensated" with reference to the temperature of 0°C (T0). The function that links the electromotive force to the temperatures T1 and T0 is a curve whose characteristics depend on the materials used in the construction of the thermocouple. Some thermocouples curves, and particularly those most reliable for the purposes of industrial readings, are those compliant with standards DIN EN 60584 and ANSI MC96.1.

### Equipment architecture

The construction of the TC66 temperature sensor is based on the following standards:

- EN 50014/18 (housing)
- Neck (1 or 2 nipple and 1 "3 union")
- EN 60584 (insert).
- Thermowells standard like: ASTM, DIN, ESSO, ENI, MONTEDISON, ENEL, etc.



The housing is in painted aluminium alloy; it is suitable to contain a transmitter and/or the ceramic block of the insert; the "Ingress Protection" is from IP66 to IP68.

The neck composed by one or two nipple and one "3 union", standard or EEx- execution, it is the extension between the head and the thermowell.

The hot junction of the thermocouple (type K or J) are positioned close to the tip of the probe. The thermocouple is available in two versions: grounded or ungrounded hot junction. The electrical structure of the thermocouple always complies with EN 60584/61515 or ANSI MC96.1/ASTM E585 standard rules.

The thermowell is from bar stock, with wetted part, conical, straight or tapered. The process connection is: threaded or flanged, in some case it can be to weld also.

Fig. 1: TC66 with the various types of process connections and end parts of the probe

### Material & Weight

Housing	Insert	Neck	Thermowell	Weight
aluminium epoxy coated	sheath in: SS 316L/1.4404 Inconel®600/2.4816	nipple and 3 union : SS 316/1.4401 or A105	thermowells: SS 316/1.4401, SS 316Ti /1.4571, (Hastelloy C276/2.4819, Monel® 400/2.4360, Inconel® 600/2.4816.)	From 1.5 to 5.0 kg for standard options

## Performance

### Operating conditions

Operating condition or test	Product type or rules		Value or data of test	
Ambient temperature	housing (without head-mounted transmitter)		-40÷130°C	
	housing (with head-mounted transmitter)		-40÷85°C	
Process temperature	It is restricted by the thermowell material:	< 600°C	SS 316L/1.4404	
		< 800°C	SS 316Ti/1.4571	
		< 1100°C	Hast.® C276/2.4819 - Inc.600®/2.4816	
Process pressure (Maximum)	The pressure values to which the thermowell can be subjected at the various temperatures are illustrated by the drawings in fig. 2.			
Maximum flow velocity	The highest flow velocity, (of the stream or of the fluid), tolerated by the thermowell, diminishes with increasing lengths, of the thermowell/probe exposed (fig. 2).			
Shock and vibration resistance test	TC Inset in according to the rule IEC 60751:	Acceleration	3 g of peak	
		Frequency	from 10Hz to 500Hz and back	
		Time test	10 hours	




Fig. 2: Pressure/temperature grafic for thermowell from bar stock

**Accuracy**

Thermocouple and range °C	EN 60584				
	Class	Max deviation	Class	Max deviation	
J (Fe-CuNi) -40° ... 750°C	2	+/-2.5°C (-40...333°C) +/-0.0075 Itl (333...750°C)	1	+/-1.5°C (-40...375°C) +/-0.004 Itl (375...750°C)	+ black - white
K (NiCr-Ni) -40 ... 1200°C	2	+/-2.5°C (-40...333°C) +/-0.0075 Itl (333...1200°C)	1	+/-1.5°C (-40...375°C) +/-0.004 Itl (375...1000°C)	+ green - white

Itl = absolute temperature value in °C

Thermocouple and range °C	ANSI MC96.1				
	Class	Max deviation	Class	Max deviation	
J (Fe-CuNi) 0 ... 750°C	Stand- ard	+/-2.2°C (0...293°C) +/-0.75% (293...750°C)	Special	+/-1.1°C (0...275°C) +/-0.4% (275...750°C)	+ black - red
K (NiCr-Ni) 0...1250°C	Stand- ard	+/-2.2°C (0...293°C) +/-0.75% (293...1250°C)	Special	+/-1.1°C (0...275°C) +/-0.4% (275...1250°C)	+ yellow - red

Itl = absolute temperature value in °C

**Others errors**

Transmitter maximum error	See the corresponding documentation (codes at the end of the document)
Display maximum error	0.1% FSR + 1 digit (FSR = Full Scale Range)

**Response time**

Tests, with the TC insert, in water at 0.4 m/s (according to IEC 60751) from 23 to 33°C:

Stem diameter of the insert	Sensing element type	Temperature of test	Response time
SS 316 - d. 6 mm	K (NiCr-Ni)	t <sub>50</sub>	2,5 s
	J (Fe-CuNi)	t <sub>90</sub>	7,0 s

**Insulation**

Measurement Insulation type	Result
Insulation resistance between terminals and probe sheath according to EN 60584, test voltage 500 V	> 1GΩ at 25°C
	> 5 MΩ at 500°C

**Self heating**

Negligible when the E+H iTEMP® transmitters are employed.

## Installation

The TC66 can be installed on pipes, tanks or other heavy duty applications, by means of threaded or flanged connections. The counterparts for process connections and gaskets, when required, are not supplied with the sensor and must be purchased separately by the user. The immersion length must take into account all the parameters of the thermometer and the process to measure. If the immersion is too low, an error may be generated in the temperature recorded due to the lower temperature of the process fluid near to the walls and heat transfer, which takes place through the sensor stem. The incidence of such an error can be not negligible if there is a big difference between the process temperature and the ambient temperature. To prevent measuring errors of this kind, it is advisable to use thermowells with a small diameter and an immersion length ( $U$ ) of at least 100–150 mm. In small section ducts the tubing's axis must be reached and preferably slightly exceeded by the tip of the probe (see fig. 3A-3C). Insulation of the outer part of the sensor reduces the effect produced by a low immersion. Alternatively, it is also possible to adopt a tilted installation (see fig. 3B-3D).




Fig. 3: Installation examples

For a best installation, in the industries, it's better to follow the rule:  $h \approx d$ ,  $L > D/2 + h$ . As far as corrosion is concerned, the base material for parts in contact with the fluid is able to withstand the most common corrosive agents up to the highest temperatures. Even the nipples and 3 elements coupling supplied with the connection fitting of the instrument are able to withstand a wide range of aggressive substances. With regard to corrosion, the base material of the wetted parts (SS 316L, SS 316Ti, Hastelloy® C276 or Inconel®600) can tolerate the common corrosive media right up to even the highest temperatures.

For further information on specific applications, contact the E+H Customer Service Department. Disassembled components of the sensors must be reassembled with the recommended clamping torques in order to ensure the appropriate IP protection class within the sensor-housing coupling.

## System components

### Housing

The protection housing, our "TA21H", commonly referred to the "connection head", is used to contain and protect the terminal block or the transmitter and to join the electric connections to the mechanical component.






Fig. 4: Housing TA21H

### Extension neck

A special extension is inserted between the husing and the thermowell connection, this part is calledneck. The neck is constituted by a tube assembled to hydraulic hardware (nipples or joints) that is suitable to allow the adjustment of the sensor to the thermowell.

In addition to the standard versions listed below, it is also possible to order the extension neck by specifying the desired length (see "Sales structure" chart at the end of this document). In the TC66 the standard lengths (N) and the versions of the extension neck can be selected among the following options:

Tp	Material	N length mm	Thread	C mm	Neck dwg type
N	316	69	1/2" NPT M	8	A
N	316	109	1/2" NPT M	8	A
NUN	316	148	1/2" NPT M	8	F
N	A105	69	1/2" NPT M	8	A
N	A105	109	1/2" NPT M	8	A
NUN	A105	148	1/2" NPT M	8	F



As illustrated by the drawing in fig. 5, the length of the extension neck may influence the temperature in the head. It is necessary that this temperature is kept within the limit values defined in the paragraph "Operating Conditions".

Before choosing the connection, it is better to verify this graphic and therefore to choose a suitable extension to avoid the heating of the head.

Fig. 5: Heating of the head caused by the process temperature

**Electronic head transmitter**

The required type of output signal can be obtained by choosing the correct head mounted transmitter. Endress+Hauser supplies "state-of-the-art" transmitters (the iTEMP® series) built in 2-wire technology and with 4...20 mA output signal, HART® or PROFIBUS-PA®. All of the transmitters can be easily programmed using a PC:

<b>Head transmitter</b>	<b>Communication software</b>
PCP TMT181	ReadWin® 2000
HART® TMT182	ReadWin® 2000, FieldCare, Hand held module DXR275, DXR375
PROFIBUS PA® TMT184	FieldCare

In the case of PROFIBUS-PA® transmitters, E+H recommends the use of PROFIBUS® dedicated connectors. The Weidmüller type is provided as a standard option. For detailed information about transmitters, please refer to the relevant documentation (refer to TI codes at the end of the document). If a head-mounted transmitter is not employed, the sensor probe may be connected through the terminal block to a remote converter (i.e. DIN rail transmitter). The customer may specify the configuration desired during the order phase. The head-mounted transmitters available are:

<b>Description</b>	<b>Dwg</b>
TMT181: PCP 4...20 mA. The TMT181 is a PC programmable transmitters  TMT182: Smart HART®. The TMT182 output consists of 4...20 mA and HART® superimposed signals.	
TMT184: PROFIBUS-PA®. For the TMT184, with PROFIBUS-PA® output signal, the communication address may be set via software or via mechanical dip-switch.	

## Thermowell

The thermowell is the component of the TC66 that must tolerate most of the mechanical stress transmitted by the process.

It is made from a round bar and supplied in different materials and dimensions, according the chemical/physical characteristics of the process: corrosion, temperature, pressure and speed of the fluid.




Fig. 6: Thermowell with threaded or flanged process connection

The thermowell consists of three parts:

- the extension neck (indicated as T), usually with a cylindrical shape (and standard diameters of 30 or 35 mm and lengths of 70/100 mm), represents the external part of the thermowell and is connected with the head of the probe by means of a neck (usually a nipple)
- the immersed part (identified as U), with a conical or cylindrical shape (the standard diameter of the area below the fitting is 20 or 25 mm), is situated next to the process connection in direct contact with the process fluid
- the threaded or flanged process connection represents the part inserted between the extension and the immersed part and guarantees the mechanical and hydraulic sealing of the thermometer and plant.

The external finishing of the thermowell stem is available with a standard value of  $Ra < 1.6 \mu\text{m}$  (different finishes are available on request).



### Warning:


The total standard length (A) of the thermowell must never exceed 1200 mm (that represents the maximum drilling limit; higher lengths are available only on request).

## Process connection

The standard process connections are threaded or flanged. When the process connection is threaded the material of connection is the same at the thermowell instead, when the process connection is flanged the material can be different: SS 316/1.4401 or ASTM A105/St 52.3.

When it is necessary to have a flange in special material, more resistant at the corrosion (example Hastelloy ®C276), it is cheaper to choose an economic version composed by a flange in SS316/1.4401 with on wetted part plated a disk in Hastelloy ®C276/2.4819 (this solution is very less expensive).

Type	Thread or Flange	$\varnothing D_1$	$\varnothing D_2$	$\varnothing D_3$	$\varnothing D_4$	D4 Nr	S1	S2	S3	A	A1
Flange	1" ANSI 150 RF SO	//	50,8	107,9	15,9	4	1,6	17,5	//	//	//
Flange	1" ANSI 300 RF SO	//	50,8	123,8	19,0	4	1,6	27,0	//	//	//
Flange	1" ANSI 600 RF SO	//	50,8	123,8	19,0	4	6,4	//	27,0	//	//
Flange	1" 1/2 ANSI 150 RF SO	//	73,0	127,0	15,9	4	1,6	22,2	//	//	//
Flange	1" 1/2 ANSI 300 RF SO	//	73,0	155,6	22,2	4	1,6	30,2	//	//	//
Flange	1" 1/2 ANSI 600 RF SO	//	73,0	155,6	22,2	4	6,4	//	31,7	//	//
Flange	2" ANSI 300 RF SO	//	92,1	165,1	19,0	8	1,6	33,3	//	//	//
Flange	2" ANSI 600 RF SO	//	92,1	165,1	19,0	8	6,4	//	36,5	//	//
All the dimension are in "mm"											
Thread	1/2" NPT	$\geq 21,4$	//	//	//	//	//	//	19,9	8,1	
Thread	3/4" NPT	$\geq 26,7$	//	//	//	//	//	//	20,2	8,6	



On request, it is possible to select also different materials, finishings and connections.

## Probe

In the TC66 the measuring probe are two:

- the TPC100 (for general purpose application)
- the TPC300 (ATEX EEx d application)

Both of the probe are made in mineral insulated cable (MgO), with sheath in AISI316/1.4401 or Inconel®600. The Immersion length (U) of the thermometer can be chosen within a standard range from 50 to 1000 mm (see "Warning" in the "thermowell" section).

The thermometer with a Immersion length (U)  $> 1000$  mm can be supplied after a technical verification of the specific applications from our technical office in the E+H Customer Service Department.

For replacement of the insert, it is necessary to refer the following table to have the IL (applicable only to standard thickness well bottoms). The immersion length of the insert spare part (IL) is calculated adding the total length of the thermowell (A = U + T) and the length of neck (N) used. Please refer the following table:

Insert general purpose	$\varnothing$ , ..mm	N , tp.	N, mm	N, material	N, thread	IL, (mm)
TPR100	6	N	69	A105/SS316	1/2"NPT M	IL = U+T+ 69 + 41
TPR100	6	N	109	A105/SS316	1/2"NPT M	IL = U+T+ 109 + 41
TPR100	6	NUN	148	A105/SS316	1/2"NPT M	IL = U+T + 148 + 41

Insert ATEX EEx d	$\varnothing$ , ..mm	N , tp.	N, mm	N, material	N, thread	IL, (mm)
TPR300	6	N	69	A105/SS316	1/2"NPT M	IL = U+T + 69 + 41
TPR300	6	N	109	A105/SS316	1/2"NPT M	IL = U+T + 109 + 41
TPR300	6	NUN	148	A105/SS316	1/2"NPT M	IL = U+T + 148 + 41




Fig. 7: Functional components, standard electrical diagrams (ceramic terminal block)

## Certificates & approvals

<b>Ex approval</b>	<ul style="list-style-type: none"> <li>■ ATEX Certificate CESI 05ATEX038 for explosion proof type of protection: ATEX II 2 GD EEx-d IIC T6..T5 T85°...T100°C. ATEX II 1/2 GD EEx-d IIC T6..T5 T85°...T100°C. The TC66 is <b>CE</b> marked.</li> </ul> <p>With regards to the NAMUR NE 24 certificate and the Manufacturer's Declaration according to the standard EN 50018, EN 50020, EN 50281-1-1, EN 50281-1-2, E+H Customer Service will be able to provide further detailed information.</p>
<b>PED approval</b>	The Pressure Equipment Directive (97/23/CE) is respected. As paragraph 2.1 of article 1 is not applicable to these types of instruments. The <b>CE</b> mark according to PED Directive is not requested.
<b>Material certification</b>	<p>The material certificate EN 10204 3.1 can be directly selected from the sale structure of the product and refers to the parts of the sensor in contact with the process fluid.</p> <p>Other types of certificates related to materials can be requested separately.</p> <p>The "short form" certificate includes a simplified declaration with no enclosures of documents related to the materials used in the construction of the single sensor and guarantees the traceability of the materials through the identification number of the thermometer.</p> <p>The data related to the origin of the materials can subsequently be requested by the client if necessary.</p>
<b>Test on thermowell</b>	<p>The pressure tests are carried out at ambient temperature in order to verify the resistance of the thermowell to the specifications indicated by the norm ASME PTC 19.3.</p> <p>With regards to the thermowells that do not comply with this norm (with a reduced tip, a tapered tip on a 9 mm tube, special dimensions, etc.), the pressure of the corresponding straight tube with similar dimensions is verified. The sensors certified for use in Ex Zones, are always tested to pressure according to the same criterions.</p>

## Further details

<b>Maintenance</b>	<p>The Omnigrad S TC66 thermometers do not require any specific maintenance.</p> <p>In the case of ATEX certified components (transmitter, insert or thermowell) please refer to the corresponding specific relevant documentation (at the end of the document).</p>
--------------------	--

## Ordering information

### Sales structure

<b>TC66-</b>	<b>Omnigrad S TC66. ATEX EEx d certified.</b> Thermocouple thermometer complete of the thermowell from bar stock. Replaceable mineral inset: grounded or ungrounded. Terminal head connection with epoxy coating, IP66/IP68 Two operating and measurement ranges: from -40 to 750°C (with TC J); -40 to 1200°C (with TC K)	
	<b>Approval:</b>	
<b>A</b>	Non-harzarus area	
<b>E</b>	*ATEX II 2 GD EEx d IIC	
<b>M</b>	*ATEX II 1/2 GD EEx d IIC	
	<b>Head, material, IP grade</b>	
<b>A</b>	TA21H Alu. epoxy coating, , IP66 /IP68	
<b>Y</b>	Special version, to be specified	
	<b>Cable entry</b>	
<b>A</b>	1 x 1/2 NPT	
<b>B</b>	2 x 1/2 NPT	
<b>C</b>	1 x 3/4 NPT	
<b>D</b>	2 x 3/4 NPT	
<b>E</b>	1 x M20 x1,5	
<b>F</b>	2 x M20 x1,5	
<b>Y</b>	Special version, to be specified	
	<b>Neck length N; Material; Fitting</b>	
<b>B</b>	69 mm, SS 316, N, 1/2"NPT M	
<b>C</b>	109 mm, SS 316, N, 1/2"NPT M	
<b>E</b>	148 mm, SS 316, NUN, 1/2"NPT M	
<b>F</b>	69 mm, A105, N, 1/2"NPT M	
<b>G</b>	109 mm, A 105, N, 1/2"NPT M	
<b>J</b>	148 mm, A 105, NUN, 1/2"NPT M	
<b>Y</b>	Special version, to be specified	
	<b>Thermowell material:</b>	
<b>B</b>	SS 316Ti	
<b>C</b>	SS 316	
<b>D</b>	SS 316L	
<b>Y</b>	Special version, to be specified	
	<b>Extension T; D1; Df; Q1; Q2</b>	
<b>1</b>	70 mm, 30 mm, 7 mm, 20 mm, 14 mm,	
<b>2</b>	75 mm, 35 mm, 7 mm, 24 mm, 14 mm,	
<b>6</b>	100 mm, 35 mm, 7 mm, 25 mm, 18 mm,	
<b>9</b>	Special version, to be specified	
	<b>Insertion Length IL:</b>	
<b>X</b>	mm	
<b>Y</b>	Special version, to be specified	
	<b>Process connection:</b>	
<b>11</b>	thread 1/2" NPT - M	
<b>22</b>	thread 3/4" NPT - M	
<b>CA</b>	1" ANSI 150 RF SO, A105	
<b>CB</b>	1" ANSI 150 RF SO, SS 316	
<b>CC</b>	1" ANSI 300 RF SO, A105	
<b>CD</b>	1" ANSI 300 RF SO, SS 316	
<b>CE</b>	1" ANSI 600 RF SO, A105	
<b>CF</b>	1" ANSI 600 RF SO, SS 316	
<b>CG</b>	1"1/2 ANSI 150 RF SO, A105	
<b>CH</b>	1" 1/2 ANSI 150 RF SO, SS 316	
<b>CI</b>	1" 1/2 ANSI 300 RF SO, A105	
<b>CK</b>	1" 1/2 ANSI 300 RF SO, SS 316	
<b>CL</b>	1" 1/2 ANSI 600 RF SO, A105	
<b>CM</b>	1" 1/2 ANSI 600 RF SO, SS 316	
<b>CQ</b>	2" ANSI 300 RF SO, A105	
<b>CS</b>	2" ANSI 600 RF SO, A105	

							<b>CT</b> 2" ANSI 300 RF SO, SS 316
							<b>CV</b> 2" ANSI 600 RF SO, SS 316
							<b>YY</b> Special version, to be specified
<b>Head transmitter; Range:</b>							
							<b>F</b> Flying leads
							<b>C</b> Terminal block
							<b>P</b> TMT181-A, PCP, from...to... °C, 2-wire, isolated
							<b>Q</b> TMT181-B, PCP ATEX, from...to... °C, 2-wire, isolated
							<b>R</b> TMT182-A, HART®, from...to... °C, 2-wire, isolated
							<b>T</b> TMT182-B, HART ®ATEX, from...to... °C, 2-wire, isolated
							<b>S</b> TMT184-A, Profibus PA®, from...to... °C, 2-wire, isolated
							<b>V</b> TMT184-B, Profibus PA® ATEX, from...to... °C, 2-wire, isolated
							<b>1</b> THT1 separate item
<b>TC Accuracy; Material:</b>							
							<b>A</b> 1x type K cl. 1 special; Inconel®600
							<b>B</b> 2x type K cl. 1 special; Inconel®600
							<b>E</b> 1x type J cl. 1 special; SS 316L
							<b>F</b> 2x type J cl. 1 special; SS 316L
							<b>Y</b> Special version, to be specified
<b>TC Standard; Hot Junction:</b>							
							<b>1</b> EN 60584; ungrounded
							<b>2</b> EN 60584; grounded
							<b>3</b> ANSI MC96.1; ungrounded
							<b>4</b> ANSI MC96.1; grounded
							<b>9</b> Special version, to be specified
<b>Additional options</b>							
							<b>0</b> Not needed
							<b>Y</b> Special version, to be specified
<b>TC66-</b>							⇐ Order code (complete)

<b>Sales structure</b>		<b>Model and version of the head transmitter</b>	
<b>THT1</b>		<b>F11</b> TMT181-A PCP, 2-wire, isolated, programmable from...to... °C	
<b>F21</b>		<b>F22</b> TMT181-B PCP ATEX, 2-wire, isolated, programmable from...to... °C	
<b>F23</b>		<b>F24</b> TMT181-C PCP FM IS, 2-wire, isolated, programmable from...to... °C	
<b>F25</b>		<b>F24</b> TMT181-D PCP CSA, 2-wire, isolated, programmable from...to... °C	
<b>L11</b>		<b>L11</b> TMT181-E PCP ATEX II3D, 2-wire, isolated, programmable from...to... °C	
<b>L21</b>		<b>L21</b> TMT181-F PCP ATEX II3D, 2-wire, isolated, programmable from...to... °C	
<b>L22</b>		<b>L22</b> TMT182-A HART®, 2-wire, isolated, programmable from...to... °C	
<b>L23</b>		<b>L23</b> TMT182-B HART® ATEX, 2-wire, isolated, programmable from...to... °C	
<b>L24</b>		<b>L24</b> TMT182-C HART® FM IS, 2-wire, isolated, programmable from...to... °C	
<b>L25</b>		<b>L25</b> TMT182-D HART® CSA, 2-wire, isolated, programmable from...to... °C	
<b>K11</b>		<b>K11</b> TMT182-E HART® II3D, 2-wire, isolated, programmable from...to... °C	
<b>K21</b>		<b>K21</b> TMT182-F HART® ATEX II3D, 2-wire, isolated, programmable from...to... °C	
<b>K22</b>		<b>K22</b> TMT184-A PROFIBUS-PA®, 2-wire, programmable from...to... °C	
<b>K23</b>		<b>K23</b> TMT184-B PROFIBUS-PA® ATEX, 2-wire, programmable from...to... °C	
<b>K24</b>		<b>K24</b> TMT184-C PROFIBUS-PA® FM IS, 2-wire, programmable from...to... °C	
<b>K25</b>		<b>K25</b> TMT184-D PROFIBUS-PA® CSA, 2-wire, programmable from...to... °C	
<b>YYY</b>		<b>YYY</b> TMT184-E PROFIBUS-PA® II3D, 2-wire, isolated, programmable from...to... °C	
<b>YYY</b>		<b>YYY</b> TMT184-F PROFIBUS-PA® ATEX CSA, 2-wire, programmable from...to... °C	
<b>YYY</b>		<b>YYY</b> Special transmitter	
		<b>Application and services</b>	
<b>1</b>		<b>1</b> Assembled into position	
<b>9</b>		<b>9</b> Special version	
<b>THT1-</b>		⇐ Order code (complete)	

## Supplementary documentation

<input type="checkbox"/> Brochure Field of activities - Temperature measurement	FA006T/09/en
<input type="checkbox"/> Temperature head transmitter iTEMP® PCP TMT181	TI070R/09/en
<input type="checkbox"/> Temperature head transmitter iTEMP® HART® TMT182	TI078R/09/en
<input type="checkbox"/> Temperature head transmitter iTEMP® PA TMT184	TI079R/09/en
<input type="checkbox"/> Industrial thermometers, RTD and Thermocouples	TI236T/02/en
<input type="checkbox"/> TC insert for temperature sensors - Omniset TPC100	TI278T/02/en
<input type="checkbox"/> TC insert for temperature sensors - Omniset TPC300 (to be released)	TI291T/02/en
<input type="checkbox"/> Safety instructions for use in hazardous areas (TPC300, to be released)	XA017T/02/en
<input type="checkbox"/> TC thermometers Omnidgrad TSC - General information	TI090T/02/en

### International Head Quarter

Endress+Hauser  
GmbH+Co. KG  
Instruments International  
Colmarer Str. 6  
79576 Weil am Rhein  
Germany

Tel. +49 76 21 9 75 02  
Fax +49 76 21 9 75 34 5  
[www.endress.com](http://www.endress.com)  
[info@ii.endress.com](mailto:info@ii.endress.com)

**Endress+Hauser**   
People for Process Automation