

WASHER THERMOCOUPLE

STYLE WT



- Maximum temperature from 400°F to 900°F (204°C to 482°C) based on wire type
- J, K and T calibrations available
- For #6, #8, #10 and 1/4" screw sizes
- Grounded or ungrounded junction
- Flexible

ORDERING INFORMATION

W T — — —

To create an ordering code fill in the boxes above with the appropriate number and/or letter from the corresponding box below.

Box 1: Calibration Code

J = J Type, ANSI Standard Tolerances

K = K Type, ANSI Standard Tolerances

T = T Type, ANSI Standard Tolerances

Box 7: Lead Wire Protection

N = None

B = SS Overbraided

Box 2: Number of Junctions

1 = Single (Standard)

2 = Duplex

Box 8: Length *fill in measurement desired*

Whole inches: 001" to 999"

(Lengths over 999" consult TTI)

Box 3: Junction*

G = Grounded

U = Ungrounded

* Dual ungrounded junctions are isolated

Box 9: Termination

A = 3/4" Stripped Leads

B = Spade Lugs

C = Spade Lugs with BX Connector

D = Standard Male Plug (350°F/177°C)

E = Medium-Temp. Male Plug (500°F/260°C)

F = High-Temp. Male Plug (800°F/426°C)

G = Standard Female Jack (350°F/177°C)

H = Medium-Temp. Female Jack (500°F/260°C)

J = High-Temp. Female Jack (800°F/426°C)

K = Miniature Male Plug (350°F/177°C)

L = Miniature Med-Temp. Male Plug (500°F/260°C)

M = Miniature Female Jack (350°F/177°C)

N = Miniature Med-Temp. Female Jack (500°F/260°C)

Box 4: Screw Size

06 = #6

08 = #8

10 = #10

14 = 1/4"

Box 5: Lead Wire Construction

A = Solid

B = Stranded

Box 10: Special Limits of Error

N = None

S = Special Tolerance Wire

Box 6: Lead Wire Insulation

G = Fiberglass (900°F/482°C)

Q = High Temp Fiberglass (1300°F/704°C)

T = Teflon (400°F/204°C)

K = Kapton (500°F/260°C)